



7103K12A2BE Information



For Reference Only

Part Number 7103K12A2BE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 20V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7103K12A2BE Specifications

| Manufacturer Part Number 7103K12A2BE Manufacturer C&K Category Switches Package - Series 7000 Circuit SPDT Switch Function On-Off-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 18.59mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | | |
|---|--------------------------------|--------------------------|
| Category Switches Package - Series 7000 Circuit SPDT Switch Function On-Off-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 18.59mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Manufacturer Part Number | 7103K12A2BE |
| Package - Series 7000 Circuit SPDT Switch Function On-Off-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 18.59mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Manufacturer | C&K |
| Package - Series 7000 Circuit SPDT Switch Function On-Off-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 18.59mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Category | Switches |
| Series 7000 Circuit SPDT Switch Function On-Off-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 18.59mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | | Toggle Switches |
| CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeLocking LeverActuator Length18.59mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Package | - |
| Switch Function On-Off-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 18.59mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Series | 7000 |
| Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Locking Lever Actuator Length 18.59mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Circuit | SPDT |
| Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeLocking LeverActuator Length18.59mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Switch Function | On-Off-On |
| Voltage Rating - DC20VActuator TypeLocking LeverActuator Length18.59mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Current Rating | 0.4VA (AC/DC) |
| Actuator Type Locking Lever Actuator Length 18.59mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Voltage Rating - AC | 20V |
| Actuator Length 18.59mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Voltage Rating - DC | 20V |
| Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Actuator Type | Locking Lever |
| Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount, Right Angle PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals | Actuator Length | 18.59mm |
| Illumination Voltage (Nominal) Mounting Type Panel Mount, Right Angle PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Illumination | Non-Illuminated |
| Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Illumination Type, Color | - |
| Termination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Illumination Voltage (Nominal) | - |
| Panel Cutout Dimensions Circular - 6.35mm Dia 1/4-40 Ingress Protection Features Circular - 6.35mm Dia 1/4-40 Epoxy Sealed Terminals | Mounting Type | Panel Mount, Right Angle |
| Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Termination Style | PC Pin |
| Ingress Protection - Features Epoxy Sealed Terminals | Panel Cutout Dimensions | Circular - 6.35mm Dia |
| Features Epoxy Sealed Terminals | Bushing Thread | 1/4-40 |
| | Ingress Protection | - |
| Report errors? | Features | Epoxy Sealed Terminals |
| | | Report errors? |

7103K12A2BE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7103K12A2BE Payment Methods



















7103K12A2BE Shipping Methods













If you have any question about 7103K12A2BE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com