

7103SDW5BE

lest a Quote

7103SDW5BE Information

| Heisener.com | Part Number | 7103SDW5BE | |
|--------------------|--------------|---|---|
| | Manufacturer | C&K | Г |
| | Category | Switches Toggle Switches | į |
| | Description | SWITCH TOGGLE SPDT 0.4VA 20V | Ś |
| | Package | - | |
| | | For the pricing/inventory/lead time, please contact | L |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7103SDW5BE Specifications

| Manufacturer Part Number 7103SDW5BE Manufacturer C&K Category Switches Category Toggle Switches Package - Series 7000 Circuit SPDT Switch Function On-Off-On Current Rating 0.4VA (ACDC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Illumination Non-Illuminated Illumination Non-Illuminated Illumination Type, Color - Termination Style Panel Mount Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/440 Ingress Protection - Features Epoxy Sealed Terminals | | |
|---|--------------------------------|------------------------|
| SwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeSandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Voltage (Nominal)-Mouting TypePael MountIllumination StyleSine MountPanel Cutour DimensionsCircular - 6.35mm DiaIllumination StyleCircular - 6.35mm DiaPanel Cutour Dimensions-Busing Thread14.40Ingress ProtectionFoxy Seaded TerminalsFeaturesExposeded Terminals | Manufacturer Part Number | 7103SDW5BE |
| Toggle SwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Youring TypePanel MountTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Manufacturer | C&K |
| Package-Series700CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VActuator TypeStandard RoundActuator TypeStandard RoundIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage Nominal)-Mouting TypePanel MountTermination StyleSire WarpPanel Cutour DimensionsCircular - 6.35mm DialBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Category | Switches |
| Series7000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | | Toggle Switches |
| CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DCStandard RoundActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpsy Sealed Terminals | Package | - |
| Switch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Length12.45mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleKire WrapPanel Actuator LengthCircular - 6.35mm DiaBushing Thread1/4-40FeaturesEpoxy Sealed Terminals | Series | 7000 |
| Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length12.45mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleKircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Circuit | SPDT |
| Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Type12.45mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleStriker Actuator Ac | Switch Function | On-Off-On |
| Voltage Rating - DC20VActuator TypeStandard RoundActuator Length12.45mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Current Rating | 0.4VA (AC/DC) |
| Actuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Voltage Rating - AC | 20V |
| Actuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Voltage Rating - DC | 20V |
| IluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination | Actuator Type | Standard Round |
| Illumination Type, Color-Illumination Yoltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminations | Actuator Length | 12.45mm |
| Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Seature S | Illumination | Non-Illuminated |
| Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Illumination Type, Color | - |
| Termination StyleWire WrapPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Illumination Voltage (Nominal) | - |
| Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Mounting Type | Panel Mount |
| Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Termination Style | Wire Wrap |
| Ingress Protection-FeaturesEpoxy Sealed Terminals | Panel Cutout Dimensions | Circular - 6.35mm Dia |
| Features Epoxy Sealed Terminals | Bushing Thread | 1/4-40 |
| | Ingress Protection | - |
| Report errors? | Features | Epoxy Sealed Terminals |
| | | Report errors? |

7103SDW5BE Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7103SDW5BE Payment Methods



If you have any question about 7103SDW5BE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com