

7103SH4W3BE

uest a Quote

7103SH4W3BE Information

Heisener.com	Part Number	7103SH4W3BE	
	Manufacturer	C&K	
	Category	Switches Toggle Switches	
	Description	SWITCH TOGGLE SPDT 0.4VA 20V	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7103SH4W3BE Specifications

Manufacturer Part Number 7103SH4W3BE Manufacturer C&K Anaufacturer Switches Category Toggle Switches Package - Scries 7000 Circuit SPT Switch Function On-Off-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 0.4VA (AC/DC) Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Illumination Type, Color - Termination Style Panel Mount Panel Cutou Dimensions Circular - 6.50mm Dia Bushing Thread Ms x 0.75 Ingress Protection - Features Epoxy Sealed Terminals		
SeriesSwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - DC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Voltage (Nominal)-Illumination Style9Panel Cuotor DimensionsGricular - 6.50mm DiaIllumination StyleSing TypePanel Cuotor DimensionsMic NorsIllumination TypedSing TypePanel Cuotor DimensionsSing TypePanel Cuotor DimensionsSing TypeFreaturesSpossaled TerminationsStates Structure StructureSing TypeStates Structure StructureSing TypeStates Structure StructureSing TypeStates Structure StructureSing StructureStructure StructureS		
Togle SwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Youring TypePanel MountTermination StyleCircular - 6.50mm DiaBushing ThreadM6x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package.Series700CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VXottage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Voltage Nominal)-Mouting TypePanel MountTermination StyleSinder Actuator LengthPanel Cutout DimensionsCircular - 6.50mm DialBushing ThreadMis NortFaturesSinder Scale Common DialStrike Strike Strik	Category	Switches
Series7000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Panel Cutout DimensionsGincurrent GuinePanel Cutout DimensionsMire WrapBushing ThreadMics 0.5Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountPanel Cutout DimensionsGircular - 6.50mm DiaBushing ThreadM6 x 0.75FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Nourting TypePanel MountTermination StyleKire WrapPanel Actuator LengthCircular - 6.50mm DiaBushing ThreadMox .FeaturesFoxy Sealed TerminalsFeaturesEpoxy Sealed Terminals	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Nonting TypePanel MountTermination StyleCircular - 6.50mm DiaBushing ThreadMis voltageIngress Protection-FeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Type10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleStriker Actuator A	Switch Function	On-Off-On
Voltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadMox 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	20V
IluminationNon-IlluminatedIlumination Type, Color-Ilumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Scaled Termination	Actuator Type	Standard Round
Illumination Type, Color-Illumination Yoltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	10.67mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	Wire Wrap
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	M6 x 0.75
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7103SH4W3BE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7103SH4W3BE Payment Methods



If you have any question about 7103SH4W3BE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com