

# 7103SYA4BE

### 7103SYA4BE Information

Heisener.com Cictul tervor carls her	Part Number Manufacturer Category Description Package	7103SYA4BE C&K Switches Toggle Switches SWITCH TOGGLE SPDT 0.4VA 20V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 7103SYA4BE Specifications

Manufacturer Part Number 7103SYA4BE   Manufacturer C&K   Category Switches   Toggle Switches Toggle Switches   Package -   Series 7000   Circuit SPDT   Switch Function On-Off-On   Current Rating 0.4VA (AC/DC)   Voltage Rating - AC 20V   Voltage Rating - DC 20V   Actuator Type Standard Round   Actuator Length Non-Illuminated   Illumination Non-Illuminated   Illumination Type, Color -   Illumination Style PC Pin   Panel Cutout Dimensions Circular - 6.35mm Dia   Bushing Thread 1/4-40   Ingress Protection -   Features Epoxy Sealed Terminates		
Switches   Toggle Switches   Package -   Series 7000   Circuit SPDT   Switch Function OnOff-On   Current Rating 04VA (AC/DC)   Voltage Rating - AC 20V   Voltage Rating - DC 20V   Actuator Type 20V   Illumination 10.67mm   Illumination Type, Color -   Illumination Voltage Nominal) -   Illumination Type, Color -   Illumination Type -   Illumin type	Manufacturer Part Number	7103SYA4BE
Toggle SwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel Mount, Right AnglePanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series700CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeSandard RoundActuator Length1067mmIlluminationNon-IlluminatedIllumination Voltage Nominal)-Mouting TypePael Mount, Right AngleIllumination StyleCircular - 6.35mm DialPanel Cutout DimensionsCircular - 6.35mm DialBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Seade Terminals	Category	Switches
Series7000CircuitSPDTSwitch FunctionOn-Off-OnCurrent RatingOn-Off-OnVoltage Rating - ACOvVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Actuator SyleSender Mange Mange Mange MangeIllumination SyleCruitar - 6.35mm DiaBashing Thread1/440Ingress Protection-FeaturesEpsy Seade Terminalis		Toggle Switches
CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fermination StylePanel Mount, Right AnglePanel Cutout DimensionsGrclina - 6.35mm DiaBushing Thread1/440Ingress Protection-FeaturesEpoxy Sealed Terminales	Package	-
<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Premination StylePanel Mount, Right AnglePanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpoxy Sealed TerminalsFeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Scaled Terminals	Switch Function	On-Off-On
Voltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCricular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionExpoy Sealed TerminalsFeaturesExpoy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	20V
IluminationNon-IluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEposy Seatures	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Length	10.67mm
Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount, Right Angle
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### 7103SYA4BE Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 7103SYA4BE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com