



## 7105K2ZGE Information

Heisener.com

Part Number 7105K2ZGE

**Manufacturer** C&K **Category** Switches

**Toggle Switches** 

**Description** SWITCH TOGGLE SPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 7105K2ZGE Specifications

| Manufacturer Part Number         7105K2ZGE           Manufacturer         C&K           Category         Switches           Package         -           Series         7000           Circuit         SPDT           Switch Function         Mom-Off-Mom           Current Rating         5A (AC/DC)           Voltage Rating - AC         120V           Voltage Rating - DC         28V           Actuator Type         Locking Lever           Actuator Length         17.88mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.35mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals |                                |                        |
|--|--------------------------------|------------------------|
| CategorySwitchesPackage-Series7000CircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals  | Manufacturer Part Number       | 7105K2ZGE              |
| Package         -           Series         7000           Circuit         SPDT           Switch Function         Mom-Off-Mom           Current Rating         5A (AC/DC)           Voltage Rating - AC         120V           Voltage Rating - DC         28V           Actuator Type         Locking Lever           Actuator Length         17.88mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.35mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals   | Manufacturer                   | C&K                    |
| Package         -           Series         7000           Circuit         SPDT           Switch Function         Mom-Off-Mom           Current Rating         5A (AC/DC)           Voltage Rating - AC         120V           Voltage Rating - DC         28V           Actuator Type         Locking Lever           Actuator Length         17.88mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.35mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals   | Category                       | Switches               |
| Series         7000           Circuit         SPDT           Switch Function         Mom-Off-Mom           Current Rating         5A (AC/DC)           Voltage Rating - AC         120V           Voltage Rating - DC         28V           Actuator Type         Locking Lever           Actuator Length         17.88mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.35mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals   |                                | Toggle Switches        |
| CircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals  | Package                        | -                      |
| Switch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals  | Series                         | 7000                   |
| Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals  | Circuit                        | SPDT                   |
| Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals   | Switch Function                | Mom-Off-Mom            |
| Voltage Rating - DC Actuator Type Locking Lever Actuator Length 17.88mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals  | Current Rating                 | 5A (AC/DC)             |
| Actuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals  | Voltage Rating - AC            | 120V                   |
| Actuator Length 17.88mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.35mm Dia  Bushing Thread 1/4-40  Ingress Protection - Features Epoxy Sealed Terminals   | Voltage Rating - DC            | 28V                    |
| Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals  | Actuator Type                  | Locking Lever          |
| Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals   | Actuator Length                | 17.88mm                |
| Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.35mm Dia  Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals   | Illumination                   | Non-Illuminated        |
| Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals   | Illumination Type, Color       | -                      |
| Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.35mm Dia  Bushing Thread 1/4-40  Ingress Protection -  Features Epoxy Sealed Terminals  | Illumination Voltage (Nominal) | -                      |
| Panel Cutout Dimensions  Circular - 6.35mm Dia  Bushing Thread  1/4-40  Ingress Protection  Features  Epoxy Sealed Terminals   | Mounting Type                  | Panel Mount            |
| Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals   | Termination Style              | Solder Lug             |
| Ingress Protection - Epoxy Sealed Terminals  | Panel Cutout Dimensions        | Circular - 6.35mm Dia  |
| Features Epoxy Sealed Terminals  | Bushing Thread                 | 1/4-40                 |
|  | Ingress Protection             | -                      |
| Report errors?   | Features                       | Epoxy Sealed Terminals |
|  |                                | Report errors?         |

#### 7105K2ZGE Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 7105K2ZGE Payment Methods





















## 7105K2ZGE Shipping Methods













If you have any question about 7105K2ZGE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com