



7105MH4ZQE Information

Heisener.com

For Reference Only

Part Number 7105MH4ZQE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7105MH4ZQE Specifications

Manufacturer Part Number 7105MH4ZQE Manufacturer C&K Category Switches Package - Scries 7000 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection - Features Epoxy Sealed Terminals		
Category Switches Package - Series 7000 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection -	Manufacturer Part Number	7105MH4ZQE
Package - Series 7000 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection -	Manufacturer	C&K
Package - Series 7000 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection -	Category	Switches
Series 7000 Circuit SPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection -		Toggle Switches
CircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-	Package	-
Switch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-	Circuit	SPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-	Switch Function	Mom-Off-Mom
Voltage Rating - DC28VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-	Current Rating	5A (AC/DC)
Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection -	Voltage Rating - AC	120V
Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Solder Lug Circular - 6.50mm Dia Circular - 6.50mm Dia	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection	Actuator Type	Standard Round
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection	Actuator Length	5.08mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread M6 x 0.75 Ingress Protection -	Mounting Type	Panel Mount
Bushing Thread M6 x 0.75 Ingress Protection -	Termination Style	Solder Lug
Ingress Protection -	Panel Cutout Dimensions	Circular - 6.50mm Dia
	Bushing Thread	M6 x 0.75
Features Epoxy Sealed Terminals	Ingress Protection	-
	Features	Epoxy Sealed Terminals
Report errors?		Report errors?

7105MH4ZQE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7105MH4ZQE Payment Methods



















7105MH4ZQE Shipping Methods













If you have any question about 7105MH4ZQE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com