

7105P3CWZQI22

7105P3CWZQI22 Information

Contract New Contract Com	Part Number Manufacturer Category Description Package	7105P3CWZQI22 C&K Switches Toggle Switches SWITCH TOGGLE SPDT 5A 120V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7105P3CWZQI22 Specifications

Manufacturer Part Number 7105P3CWZQ122 Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit SPDT Switch Function Mom-Off-Mom Curren Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Solder Lug Mounting Type Solder Lug Panel Mount Solder Lug Ingress Protection Flort - G.Stmm Dia Bushing Thread 1/4-40 Ingress Protection Black Actuator		
CategorySwitchesPackage-Series7000CircuitSPDTSwitch FunctionMon-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC88VActuator TypeFlat Anti-RotationIlluminationNon-IlluminatedIllumination Type, Color-Illumination Type, ColorSolder LugMounting TypeSolder LugPanel Cutout DimensionsCircular - 6.55mm DiaBushing Thread1/440Ingress ProtectionP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Manufacturer Part Number	7105P3CWZQI22
Toggle SwitchesPackage-Series7000CircuitSPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Type11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/440Ingress ProtectionFlor Antiaget, WaterproofFeaturesBlack Actuator	Manufacturer	C&K
Package-Series7000CircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC84VActuator TypeFlat Anti-RotationActuator Length1.1.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionBack ActuatorFeaturesBack Actuator	Category	Switches
Series7000CircuitSPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length1.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular 6.35mm DiaBushing Thread1/440Ingress ProtectionBack ActuatorFeaturesBlack Actuator		Toggle Switches
CircuitSPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length1.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fremination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionBick ActuatorFeaturesBick Actuator	Package	-
Switch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSa VActuator TypeFlat Anti-RotationActuator Length1.43mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeSolder LugPanel Actuator SyleSolder LugInding Thread1/4-40Bushing Thread1/4-40FatereseSider Steppen S	Series	7000
Current RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length1.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Premination StyleSolder LugPanel MountSolder LugBushing Thread1/4-40Ingress ProtectionBick ActuatorFeaturesBick Actuator	Circuit	SPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length1.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugTermination StyleSolder LugBushing Thread1/440Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Switch Function	Mom-Off-Mom
Voltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionBlack ActuatorFeaturesBlack Actuator	Current Rating	5A (AC/DC)
Actuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionBlack Actuator	Voltage Rating - AC	120V
Actuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionPhots Tight, WaterproofFeaturesBlack Actuator	Voltage Rating - DC	28V
IluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Actuator Type	Flat Anti-Rotation
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Actuator Length	11.43mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Termination Style	Solder Lug
Ingress ProtectionIP67 - Dust Tight, WaterproofFeaturesBlack Actuator	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Black Actuator	Bushing Thread	1/4-40
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	Black Actuator
		Report errors?

7105P3CWZQI22 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7105P3CWZQI22 Payment Methods





If you have any question about 7105P3CWZQI22, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com