

7107MPDZBE

7107MPDZBE Information

Heisener.com	Part Number Manufacturer Category Description Package	7107MPDZBE C&K Switches Toggle Switches SWITCH TOGGLE SPDT 0.4VA 20V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7107MPDZBE Specifications

Manufacturer Part Number 7107MPDZBE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit SPDT Switch Function On-Off-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Anti-Rotation Illumination Son-Minimated Illumination Son-Minimated Illumination Type, Color - Illumination Voltage (Nominal) Solder Lug Youting Type Solder Lug Illumination Style Solder Lug Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesToggle SwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugNouting TypeSolder LugBushing Thread1/440Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7107MPDZBE
Toggle SwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series700CircuitSPDTSwitch FunctionOn-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length6.86mmIluminationNon-IlluminatedIlumination Voltage (Nominal)-Mouting TypeSolder LugMouting TypeSolder LugIngense NoticeSolder LugIngense NoticeSolder LugIngense Notice-Ingense Notice-Ingense Notice-FaturesSpot Sealed TerminalsFaturesEpoty Sealed Terminals	Category	Switches
Series7000CircuitSPDTSwitch FunctionOn-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fermination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread1/440Ingress Protection-FeaturesEpoxy Sealed Tremination		Toggle Switches
CircuitSPDTSwitch FunctionOn-Off-MomCurrent RatingOn-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Type6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugIngens Protection1/4-40Ingens Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Panel Mounting TypeSolder LugPanel Mounting TypeSolder LugInternination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionFayos Solder Sol	Circuit	SPDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length6.86mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeSolder LugTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpsy Sealed TerminalsFeaturesEpsy Sealed Terminals	Switch Function	On-Off-Mom
Voltage Rating - DC20VActuator TypeAnti-RotationActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeAnti-RotationActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	20V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Seature Seatur	Actuator Type	Anti-Rotation
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	6.86mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7107MPDZBE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7107MPDZBE Payment Methods





If you have any question about 7107MPDZBE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com