



7109MY9V6BE Information

Heisener.com

Part Number 7109MY9V6BE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 20V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7109MY9V6BE Specifications

Manufacturer Part Number 7109MY9V6BE Manufacturer C&K Category Switches Package - Series 7000 Circuit SPDT Switch Function On-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Features		
CategorySwitchesPackage-Series7000CircuitSPDTSwitch FunctionOn-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-	Manufacturer Part Number	
Package - Circuit SPDT Switch Function On-Mom Current Rating O.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 5.08mm Illumination Woltage (Nominal) Illumination Voltage (Nominal) Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions Bushing Thread Ingress Protection Toggle Switches - Company Company Company Through Godon - Company Company Through Hole Termination Style PC Pin Panel Cutout Dimensions - Company Company Thread Unthreaded Ingress Protection	Manufacturer	C&K
Package - Series 7000 Circuit SPDT Switch Function On-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection -	Category	Switches
Series7000CircuitSPDTSwitch FunctionOn-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-		Toggle Switches
Circuit SPDT Switch Function On-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions Bushing Thread Unthreaded Ingress Protection -	Package	-
Switch FunctionOn-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-	Series	7000
Current Rating Voltage Rating - AC 20V Voltage Rating - DC Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC 20V Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Ingress Protection 20V 20V Tended Tended 100 Tended 20V Tended Tended 100 Tende	Switch Function	On-Mom
Voltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-	Current Rating	0.4VA (AC/DC)
Actuator Type Standard Round Actuator Length 5.08mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection -	Voltage Rating - AC	20V
Actuator Length Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Ingress Protection 5.08mm Non-Illuminated - Unthreaded 5.08mm Non-Illuminated - Unthreaded 5.08mm Non-Illuminated - Unthreaded	Voltage Rating - DC	20V
Illumination Type, Color - Illumination Voltage (Nominal) - Through Hole Termination Style PC Pin Panel Cutout Dimensions - Sushing Thread Unthreaded Ingress Protection - Von Month	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - - - - - - - - - - - - -	Actuator Length	5.08mm
Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-	Illumination	Non-Illuminated
Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Through Hole PC Pin	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection -	Mounting Type	Through Hole
Bushing Thread Unthreaded Ingress Protection -	Termination Style	PC Pin
Ingress Protection -	Panel Cutout Dimensions	-
	Bushing Thread	Unthreaded
Energy Cooled Terminals	Ingress Protection	-
reatures Epoxy Seared Terminals	Features	Epoxy Sealed Terminals
Report errors?		Report errors?

7109MY9V6BE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7109MY9V6BE Payment Methods



















7109MY9V6BE Shipping Methods













If you have any question about 7109MY9V6BE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com