



7109P3Y4ZQE Information

Heisener com

Part Number 7109P3Y4ZQE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7109P3Y4ZQE Specifications

Manufacturer Part Number 7109P3Y4ZQE Manufacturer C&K Category Switches Package - Series 7000 Circuit SPDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
Category Switches Package - Series 7000 Circuit SPDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Manufacturer Part Number	7109P3Y4ZQE
Package - 7000 Circuit SPDT Switch Function On-Mom Current Rating	Manufacturer	C&K
Package - Series 7000 Circuit SPDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
Series 7000 Circuit SPDT Switch Function On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Switch Function	On-Mom
Voltage Rating - DC Actuator Type Flat Anti-Rotation Actuator Length Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Flat Anti-Rotation
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	11.43mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7109P3Y4ZQE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7109P3Y4ZQE Payment Methods



















7109P3Y4ZQE Shipping Methods













If you have any question about 7109P3Y4ZQE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com