



712RAH Information

Heisener.com

Part Number 712RAH

Manufacturer Switchcraft Inc.

Category Connectors, Interconnects

Barrel - Power Connectors

Description JACK, 2.5MM PIN, SHORT BUSHING,

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









712RAH Specifications

Manufacturer Part Number712RAHManufacturerSwitchcraft Inc.CategoryConnectors, InterconnectsBarrel - Power ConnectorsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.50mm ID (0.098"), 5.50mm OD (0.217")Actual Diameter0.098" (2.50mm ID), 0.217" (5.50mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single SwitchMounting TypeThrough Hole, Right AngleMounting FeatureBulkhead - Front Side NutTerminationSolder Eyelet(s)ShieldingUnshieldedFeaturesMounting Hardware, Thread LockInsulation Color-Voltage - Rated-Current Rating-Report errors?		
CategoryConnectors, InterconnectsPackage-Series-Connector TypeJackGenderMaleIndustry Recognized Mating Diameter2.50mm ID (0.098"), 5.50mm OD (0.217")Actual Diameter0.098" (2.50mm ID), 0.217" (5.50mm OD)Number of Positions/Contacts2 Conductors, 3 ContactsInternal Switch(s)Single SwitchMounting TypeThrough Hole, Right AngleMounting FeatureBulkhead - Front Side NutTerminationSolder Eyelet(s)ShieldingUnshieldedFeaturesMounting Hardware, Thread LockInsulation Color-Voltage - Rated-Current Rating-	Manufacturer Part Number	712RAH
Package - Connector Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch Mounting Type Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated Current Rating	Manufacturer	Switchcraft Inc.
Package - Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch Mounting Type Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated Current Rating	Category	Connectors, Interconnects
Series - Connector Type Jack Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch Mounting Type Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated - Current Rating -		Barrel - Power Connectors
Connector Type Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch Mounting Type Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated Current Rating - Jack Male Male Jack Male Lospan Jack Mountin Diameter Solmm ID (0.098"), 5.50mm OD (0.217") Solmm ID (0.098"), 5.50mm OD (0.217") Jonath Color Voltage - Rated - Current Rating	Package	-
Gender Male Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch Mounting Type Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated - Current Rating -	Series	-
Industry Recognized Mating Diameter 2.50mm ID (0.098"), 5.50mm OD (0.217") Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch Mounting Type Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated - Current Rating - 2.50mm ID (0.098"), 5.50mm OD (0.217") 0.098" (2.50mm ID), 0.217" (5.50mm OD) 0.098" (2.50mm ID)	Connector Type	Jack
Actual Diameter 0.098" (2.50mm ID), 0.217" (5.50mm OD) Number of Positions/Contacts 2 Conductors, 3 Contacts Internal Switch(s) Single Switch Mounting Type Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated - Current Rating -	Gender	Male
Number of Positions/Contacts Internal Switch(s) Single Switch Mounting Type Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color Voltage - Rated - Current Rating - Current Rating	Industry Recognized Mating Diameter	2.50mm ID (0.098"), 5.50mm OD (0.217")
Internal Switch(s) Mounting Type Through Hole, Right Angle Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Unshielded Features Mounting Hardware, Thread Lock Insulation Color Voltage - Rated Current Rating	Actual Diameter	0.098" (2.50mm ID), 0.217" (5.50mm OD)
Mounting Type Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Unshielded Features Mounting Hardware, Thread Lock Insulation Color Voltage - Rated Current Rating Through Hole, Right Angle Bulkhead - Front Side Nut Solder Eyelet(s) - Unshielded	Number of Positions/Contacts	2 Conductors, 3 Contacts
Mounting Feature Bulkhead - Front Side Nut Termination Solder Eyelet(s) Unshielded Features Mounting Hardware, Thread Lock Insulation Color Voltage - Rated Current Rating Bulkhead - Front Side Nut Solder Eyelet(s) Unshielded	Internal Switch(s)	Single Switch
Termination Solder Eyelet(s) Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated - Current Rating -	Mounting Type	Through Hole, Right Angle
Shielding Unshielded Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated - Current Rating -	Mounting Feature	Bulkhead - Front Side Nut
Features Mounting Hardware, Thread Lock Insulation Color - Voltage - Rated - Current Rating -	Termination	Solder Eyelet(s)
Insulation Color - Voltage - Rated - Current Rating -	Shielding	Unshielded
Voltage - Rated - Current Rating -	Features	Mounting Hardware, Thread Lock
Current Rating -	Insulation Color	-
•	Voltage - Rated	-
Report errors?	Current Rating	-
		Report errors?

712RAH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

712RAH Payment Methods



















712RAH Shipping Methods













If you have any question about 712RAH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com