

714-43-232-31-018000

714-43-232-31-018000 Information

Henercom	 714-43-232-31-018000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 32POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



714-43-232-31-018000 Specifications

Manufacturer Mill-Max Manufacturing Corp. Category Connectors, Interconnects Sockets for ICs, Transistors Sockets for ICs, Transistors Package - Series 714 Type DIP, 0.1" (2.54mm) Row Spacing Number of Positions or Pins (Grid) 32 (2 x 16) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating 30µin (0.76µm) Contact Material - Mating Beryllium Copper Mounting Type Through Hole Features Closed Frame Contact Finish - Post Gold Contact Finish - Post Gold Contact Finish Thickness - Post Gold Contact Finish - Post Gold Contact Finish - Post Gold Contact Finish Thickness - Post Gold Contact Material - Post Gold Contact Material - Post Gold			
CategoryConnectors, Interconnects Sockets for ICs, TransistorsPackage-Series714TypeDIP, 0.1" (2.54mm) Row SpacingNumber of Positions or Pins (Grid)32 (2 x 16)Ottor (2.54mm)0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish Thickness - Post30µin (0.76µm)Contact Finish Thickness - PostSolderContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostGoldContact Material - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostGoldContact Material - PostGoldContact Material - PostSolycin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Manufacturer Part Number	714-43-232-31-018000	
NumberSockets for ICs, TransistorsPackage-Series714TypeDIP, 0.1" (2.54mm) Row SpacingNumber of Positions or Pins (Grid)32 (2 x 16)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish - PostSolderContact Finish Thickness - PostGoldContact Finish Thickness - PostSoldin (0.76µm)Contact Finish Thickness - PostSolderPitch - PostGoldContact Finish Thickness - PostSolderContact Finish Thickness - PostSolyin (0.76µm)Contact Material - PostSolyin (0.76µm)Contact Finish Thickness - PostSolyin (0.76µm)Contact Finish Thickness - PostSolyin (0.76µm)Contact Finish Thickness - PostSolyin (0.76µm)Contact Material	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series714TypeDIP, 0.1" (2.54mm) Row SpacingNumber of Positions or Pins (Grid)32 (2 x 16)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - Post30µin (0.76µm)Potact Finish Thickness - PostSolderContact Finish Thickness - PostSolderContact Finish Thickness - PostSoly (2.54mm)Contact Finish Thickness - PostSoly (0.76µm)Contact Material - PostSoly (0.76µm)Contact Material - PostSoly (0.76µm)Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
Yea714TypeDIP, 0.1" (2.54mm) Row SpacingNumber of Positions or Pins (Grid)32 (2 x 16)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish - PostOldContact Finish Thickness - PostSolderContact Finish Thickness - PostSoldin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C		Sockets for ICs, Transistors	
Type DIP, 0.1" (2.54mm) Row Spacing Number of Positions or Pins (Grid) 32 (2 x 16) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Contact Material - Mating Beryllium Copper Mounting Type Through Hole Features Closed Frame Termination Solder Pitch - Post 0.100" (2.54mm) Contact Finish Thickness - Post Gold Contact Finish Thickness - Post Solder Contact Finish Thickness - Post Solynin (0.76µm) Contact Finish Thickness - Post Solynin (0.76µm) Contact Finish Thickness - Post Solynin (0.76µm) Contact Material - Post Solynin (0.76µm) Contact Material - Post Brass Alloy Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester Operating Temperature -55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid)32 (2 x 16)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - NostGoldContact Finish - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostGoldContact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Series	714	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post30µin (0.76µm)Contact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Туре	DIP, 0.1" (2.54mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post30µin (0.76µm)Contact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	32 (2 x 16)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Features	Closed Frame	
Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Gold	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	30µin (0.76µm)	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Report errors?	Operating Temperature	-55°C ~ 125°C	
			Report errors?

714-43-232-31-018000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

714-43-232-31-018000 Payment Methods WIRE transfer PayPal Methods 714-43-232-31-018000 Shipping Methods Feelex. I Control Control

If you have any question about 714-43-232-31-018000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com