

714-43-240-31-018000

714-43-240-31-018000 Information

And Isener.com	 714-43-240-31-018000 Mill-Max Manufacturing Corp. Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 40POS GOLD - For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdent@heisener.com	Request a Quote

E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



714-43-240-31-018000 Specifications

Manufacturer Part Number714-43-240-31-018000ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series714TypeDIP, 0.1" (2.54mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Mounting TypeHrough HoleFeaturesClosed FrameTornationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeGlodaGoldContact Finish Thicknes - MatingGoldContact Finish ThicknesGoldGoldaContact Finish Thicknes - MatingSolderGontact Finish Thicknes - MatingSolderGontact Finish Thicknes - MatingSolderGontact Finish Thicknes - MatingSolderFeaturesGoldContact Finish - PostGoldContact Finish - PostSoluin (0.76µm)Contact Finish Thickness - PostSolµin (0.76µm)Contact Finish Thickness - PostSolµin (0.76µm)Gontact Finish Thickness - PostSolµin (0.76µm)Contact Finish Thickness - PostSolµin (0.76µm)Gontact Finish Thickness - PostSolµin (0.76µm)Gontact Finish Thickness - PostSolµin (0.76µm)Gontact Finish Thickness - PostSolµin (0.76µm)Gonta			
CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackage-Series714TypeDIP, 0.1" (2.54mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Katerial - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - NatingSolderGoldContact Finish Thicknes - MatingGoldContact Material - MatingGoldContact Material - MatingGolderClosed FrameContact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - PostSolyin (0.76µm)Contact Finish Thickness - PostSolyin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terepthhalate (PCT), PolyesterPoreating Temperature-55°C ~ 125°C	Manufacturer Part Number	714-43-240-31-018000	
NumberSockets for ICs, TransistorsPackage-Series714TypeDIP, 0.1" (2.54mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameFreminationSolderContact Finish - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - Post30µin (0.76µm)Contact Finish - PostSolderContact Finish Thickness - PostBigli (0.76µm)Contact Finish - PostSolderContact Finish Thickness - PostBigli (0.76µm)Contact Finish Thickness - PostBigli (0.76µm)Contact Finish Thickness - PostBigli (0.76µm)Contact Finish Thickness - PostSolyin (0.76µm) <td>Manufacturer</td> <td>Mill-Max Manufacturing Corp.</td> <td></td>	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series714TypeDIP,0.1" (2.54mn) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mn) Row SpacingContact Finish - MatingGoldContact Finish Thickness - MatingSolpin (0.76µm)Contact Material - MatingBeryliun CopperMounting TypeThrough HoleFeaturesColed FrameFeaturesSolderContact Finish - Post0.100" (2.54mn)Contact Finish - PostSolderContact Finish - PostGoldContact Finish - PostSolderContact Finish - PostGoldContact Finish - PostSolpin (0.76µm)Contact Finish Thickness - PostSolpin (0.76µm) <td>Category</td> <td>Connectors, Interconnects</td> <td></td>	Category	Connectors, Interconnects	
Series 714 Type DIP, 0.1" (2.54mm) Row Spacing Number of Positions or Pins (Grid) 40 (2 x 20) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating 30µin (0.76µm) Contact Material - Mating Beryllium Copper Mounting Type Through Hole Features Closed Frame Pitch - Post 0.100" (2.54mm) Pitch - Post Solder Potact Finish Thickness - Post Gold Potact Finish - Post 0.100" (2.54mm) Contact Finish - Post Solder Contact Finish - Post Gold Contact Finish Thickness - Post Gold Contact Finish Thickness - Post Solpin (0.76µm) Contact Material - Post Solpin (0.76µm) Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester Polycyclohexylenedimethylene Terephthalate (PCT), Polyester -55°C ~ 125°C		Sockets for ICs, Transistors	
TypeDIP, 0.1" (2.54mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FramePitch - Post0.100" (2.54mm)Contact Finish Thickness - NotSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish Thickness - PostSolderContact Finish Thickness - PostSoldin (0.76µm)Contact Material - Post0.100" (2.54mm)Contact Finish Thickness - PostSoldin (0.76µm)Housing MaterialPolycylohexylenedimethylene Terephthalate (PCT), PolyesterPiogerating Temperature-55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Finish Thickness - Post30µin (0.76µm)Contact Finish Thickness - Post30µin (0.76µm)Contact Material - Post30µin (0.76µm)Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Series	714	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Finish Thickness - PostSolyin (0.76µm)Housing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterPorenting Temperature-55°C ~ 125°C	Туре	DIP, 0.1" (2.54mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllum CopperMounting TypeThrough HoleFeaturesClosed FrameFeaturesSolderTerminationSolderPitch - Post0.100° (2.54mm)Contact Finish - PostGoldContact Finish - Post30µin (0.76µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostForsey Contact SolderContact Finish Thickness - PostSolderContact Finish - PostSolder<	Number of Positions or Pins (Grid)	40 (2 x 20)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesClosed FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostGoldContact Finish Thickness - Post30μin (0.76μm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Features	Closed Frame	
Contact Finish - PostGoldContact Finish Thickness - Post30μin (0.76μm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Post30µin (0.76µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Gold	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	30µin (0.76µm)	
Operating Temperature -55°C ~ 125°C	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
	Operating Temperature	-55°C ~ 125°C	
Report errors'			Report errors?

714-43-240-31-018000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

714-43-240-31-018000 Payment Methods





If you have any question about 714-43-240-31-018000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com