

7141-12-1001 Information

Heisener.com

Part Number 7141-12-1001
Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPDT 250MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7141-12-1001 Specifications

Manufacturer Part Number7141-12-1001ManufacturerCoto TechnologyCategoryRelaysPackage-Series7000Relay TypeReedCoil TypeNon LatchingCoil Current10.9mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time2msRelease Time2.5msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin		
Category Relays Backage - Series 7000 Relay Type Reed Coil Type Non Latching Coil Current 10.9mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 150VAC, 150VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 2ms Release Time 2.5ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Manufacturer Part Number	7141-12-1001
Package-Series7000Relay TypeReedCoil TypeNon LatchingCoil Current10.9mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time2msRelease Time2.5msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Coto Technology
Package-Series7000Relay TypeReedCoil TypeNon LatchingCoil Current10.9mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time2msRelease Time2.5msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series 7000 Relay Type Reed Coil Type Non Latching Coil Current 10.9mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 150VAC, 150VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 2ms Release Time 2.5ms Features Diode Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current10.9mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time2msRelease Time2.5msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current10.9mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)250mASwitching Voltage150VAC, 150VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time2msRelease Time2.5msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Series	7000
Coil Current 10.9mA 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 150VAC, 150VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 2ms Release Time 2.5ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 150VAC, 150VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 2ms Release Time 2.5ms Features Diode Mounting Type Through Hole Termination Style	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 250mA Switching Voltage 150VAC, 150VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 2ms Release Time 2.5ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Coil Current	10.9mA
Contact Rating (Current) Switching Voltage 150VAC, 150VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 2ms Release Time 2.5ms Features Diode Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage 150VAC, 150VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 2ms Release Time 2.5ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 1 VDC Operate Time 2 ms Release Time 2.5 ms Features Diode Mounting Type Through Hole Termination Style	Contact Rating (Current)	250mA
Turn Off Voltage (Min) Operate Time 2ms Release Time 2.5ms Features Diode Mounting Type Through Hole Termination Style 1 VDC 2ms 2.5ms PC Pin	Switching Voltage	150VAC, 150VDC - Max
Operate Time2msRelease Time2.5msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9 VDC
Release Time2.5msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	1 VDC
Features Diode Mounting Type Through Hole Termination Style PC Pin	Operate Time	2ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	2.5ms
Termination Style PC Pin	Features	Diode
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

7141-12-1001 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7141-12-1001 Payment Methods



















7141-12-1001 Shipping Methods













If you have any question about 7141-12-1001, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com