

715P222516LD3

715P222516LD3 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



715P222516LD3 Specifications

SeriesOrange Drop? 715PCapacitance2200pFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.642" (16.30mm)Height - Seated (Max)0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-			
CategoryCapacitorsPackageRadialPackageRadialSeriesOrange Drop? 715PCapacitance2200pFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproplene (PP), MetallizedSSR (Equivalent Series Resistance)-Operating Temperature55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.642" (16.30mm)Height - Seated (Max)0.642" (16.30mm)Lead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Manufacturer Part Number	715P222516LD3	
Filn CapacitorsPackageRadialSeriesOrange Drop? 715PCapacitance2200pFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.642" (16.30mm)Height - Seated (Max)0.642" (16.30mm)PC Pins1.200" (18.30mm)ApplicationsMigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Manufacturer	Cornell Dubilier Electronics (CDE)	
PackageRadiaSeriesOrange Drop? 715PCapacitance2200pFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.642" (16.30mm)Height - Seated (Max)0.642" (16.30mm)ApplicationsMigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Category	Capacitors	
Series Orange Drop? 715P Capacitance 2200pF Tolerance ±5% Voltage Rating - AC 500V Voltage Rating - DC 1600V (1.6kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 85°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.642" (16.30mm) Height - Seated (Max) 0.720" (18.30mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -		Film Capacitors	
Capacitance2200pFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.642" (16.30mm)Height - Seated (Max)0.642" (18.30mm)Lead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Package	Radial	
Tolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.642" (16.30mm)Height - Seated (Max)0.720" (18.30mm)Lead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Series	Orange Drop? 715P	
Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.350" Dia x 1.252" L (8.90mm x 31.80mm)Height - Seated (Max)Of 20' (16.30mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Capacitance	2200pF	
Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.350° Dia x 1.252" L (8.90mm x 31.80mm)Height - Seated (Max)0.642" (16.30mm)Termination0.720" (18.30mm)Lead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Tolerance	$\pm 5\%$	
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.350" Dia x 1.252" L (8.90mm x 31.80mm)Height - Seated (Max)0.642" (16.30mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Voltage Rating - AC	500V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.350" Dia x 1.252" L (8.90mm x 31.80mm)Height - Seated (Max)0.642" (16.30mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Voltage Rating - DC	1600V (1.6kV)	
Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.350" Dia x 1.252" L (8.90mm x 31.80mm)Height - Seated (Max)0.642" (16.30mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Dielectric Material	Polypropylene (PP), Metallized	
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.350" Dia x 1.252" L (8.90mm x 31.80mm)Height - Seated (Max)0.642" (16.30mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.350" Dia x 1.252" L (8.90mm x 31.80mm)Height - Seated (Max)0.642" (16.30mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Operating Temperature	-55°C ~ 85°C	
Size / Dimension0.350" Dia x 1.252" L (8.90mm x 31.80mm)Height - Seated (Max)0.642" (16.30mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)0.642" (16.30mm)TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Package / Case	Radial	
TerminationPC PinsLead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Size / Dimension	0.350" Dia x 1.252" L (8.90mm x 31.80mm)	
Lead Spacing0.720" (18.30mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Height - Seated (Max)	0.642" (16.30mm)	
Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Termination	PC Pins	
Features -	Lead Spacing	0.720" (18.30mm)	
	Applications	High Frequency, Switching; High Pulse, DV/DT; Snubber	
Report errors?	Features	-	
			Report errors?

715P222516LD3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

715P222516LD3 Payment Methods





If you have any question about 715P222516LD3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com