

715P22396KA3

est a Quote

715P22396KA3 Information

Heisener.com	Part Number	715P22396KA3	
	Manufacturer	Cornell Dubilier Electronics (CDE)	
	Category	Capacitors Film Capacitors	
	Description	CAP FILM 0.022UF 10% 600VDC RAD	
	Package	Radial	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



715P22396KA3 Specifications

Manufacturer Cornell Dubilier Electronics (CDE) Capacitors Eilm Capacitors Package Radial Series Orange Drop? 715P Capacitance 0.022µF Tolerance ±10% Voltage Rating - AC 200V Voltage Rating - DC 600V Dielectric Material Polypropylene (PP), Metallized Poprating Temperature -55°C ~ 85°C Mounting Type Through Hole Size / Dimension 0.480° Dia x 0.902° L (12.20mm x 22.90mm) Height - Seated (Max) 0.772° (19.60mm) Termination PC Pins Lead Spacing -689° (17.50mm) Applications High Frequency, Switching; High Pulse, DV/DT; Snubber			
CategoryCapacitorsPackageRadialPackageRadialSeriesOrange Drop? 715PCapacitance0.022 µFTolerance±10%Voltage Rating - AC200 VVoltage Rating - DC600 VDielectric MaterialPolypropylene (PP), MetallizedSeries-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480° Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689° (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Manufacturer Part Number	715P22396KA3	
Filn CapacitorsPackageRadialSeriesOrange Drop? 715PCapacitance0.022µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC600VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480° Dia x 0.902° L (12.20mm x 22.90mm)Height - Seated (Max)0.772° (19.60mm)Pc PinsLead SpacingApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Manufacturer	Cornell Dubilier Electronics (CDE)	
PackageRadiaPackageRadiaSeriesOrange Drop? 715PCapacitance0.022μFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC600VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480° Dia x 0.902° L (12.20mm x 22.90mm)Height - Seated (Max)0.772° (19.60mm)Lead Spacing0.689° (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Category	Capacitors	
SeriesOrange Drop? 715PCapacitance0.022µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC600VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480° Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-		Film Capacitors	
Capacitance0.022µFTolerance±10%Voltage Rating - AC200VVoltage Rating - DC600VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480° Dia x 0.902° L (12.20mm x 22.90mm)Height - Seated (Max)0.772° (19.60mm)TerminationPC PinsLead Spacing0.689° (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Package	Radial	
Tolerance±10%Voltage Rating - AC200VVoltage Rating - DC600VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-S5°C ~ 85°CMounting TypeHrough HolePackage / Case0.480° Dia x 0.902° L (12.20mm x 22.90mm)Size / Dimension0.772° (19.60mm)Height - Seated (Max)0.689° (17.50mm)Lead Spacing0.689° (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Series	Orange Drop? 715P	
NoticeHighVoltage Rating - AC200VVoltage Rating - DC600VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480" Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Capacitance	0.022µF	
Voltage Rating - DC600VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480" Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Tolerance	±10%	
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480" Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Voltage Rating - AC	200V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480" Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Voltage Rating - DC	600V	
Operating Temperature-55°C ~ 85°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480" Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Dielectric Material	Polypropylene (PP), Metallized	
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.480" Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.480" Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Operating Temperature	-55°C ~ 85°C	
Size / Dimension0.480" Dia x 0.902" L (12.20mm x 22.90mm)Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)0.772" (19.60mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Package / Case	Radial	
TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Size / Dimension	0.480" Dia x 0.902" L (12.20mm x 22.90mm)	
Lead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, Switching; High Pulse, DV/DT; SnubberFeatures-	Height - Seated (Max)	0.772" (19.60mm)	
Applications High Frequency, Switching; High Pulse, DV/DT; Snubber Features -	Termination	PC Pins	
Features -	Lead Spacing	0.689" (17.50mm)	
	Applications	High Frequency, Switching; High Pulse, DV/DT; Snubber	
Report errors?	Features	-	
1			Report errors?

715P22396KA3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

715P22396KA3 Payment Methods





If you have any question about 715P22396KA3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com