

7201K12V3QE

a Quote

7201K12V3QE Information

同とう
100
2277
- E
ntact
Request
1

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7201K12V3QE Specifications

Manufacturer Part Number 7201 K12V3QE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit DPDT Switch Function On-On Current Rating SA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length Non-Illuminated Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Actuator Length PC Pin Illumination Style PC Pin Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
SwitchesPackage-Series700Circuit0PDTSwitch Function0n-OnCurrent RatingSA (AC/DC)Voltage Rating - AC28VActuator Type28VActuator Length18.59mmIllumination-Illumination Type, Color-Munting Type-Munting TypePice IndexIllumination Style-Panel Cutor DimensionsCircular - 6.35mm DiaIllumination Style-Panel Cutor Dimensions-Rating Thread1/-40Rates Protection-FaturesExposed TerminationsString Thread-String Thread-FaturesExposed TerminationsString Thread-String Thread-	Manufacturer Part Number	7201K12V3QE
Togle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length18.59mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Youting TypePanel MountTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series700CircuitDPDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeIcking LeverActuator LengthNon-IlluminatedIlluminationNon-IlluminatedIllumination Voltage (Nominal)-Mouting TypePerinIndustry StyleCircular - 6.35mm DialIndustry StyleCircular - 6.35mm DialIllumination StylePerinPanel Cutout DimensionsCircular - 6.35mm DialBushing Thread1.4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
Series7000CircuitDPDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length18.59mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Panel Cutout DimensionsPanel MountPanel Cutout DimensionsCircular - A.35mm DiaBushing Thread14.40Ingress Protection-FeaturesEpsy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC100VVoltage Rating - DC28VActuator TypeLocking LeverActuator LengthNon-IlluminatedIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Actuator StylePanel MountPanel Cutour DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpsy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeIcoking LeverActuator Length18.59mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Inges Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeIocking LeverActuator Length18.59mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Nonting TypePanel MountTermination StyleCircular - 6.35mm DiaBushing ThreadJiccular - 6.35mm DiaIngress Protection-FeaturesEgoxy Seader JennicalsFeaturesEgoxy Seader Jennicals	Circuit	DPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length18.59mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleCricular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC28VActuator TypeLocking LeverActuator LengthI8.59mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator TypeLocking LeverActuator Length18.59mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoys Saled Terminals	Voltage Rating - AC	120V
Actuator Length18.59mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	28V
IluminationNon-IlluminatedIlumination Type, Color-Ilumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Scaled Termination	Actuator Type	Locking Lever
Illumination Type, Color-Illumination Yoltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Length	18.59mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7201K12V3QE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7201K12V3QE Payment Methods





If you have any question about 7201K12V3QE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com