



7201K9A3QE Information

Heisener.com

Part Number 7201K9A3QE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7201K9A3QE Specifications

Manufacturer Part Number 7201K9A3QE Manufacturer C&K Category Switches Package - Series 7000 Circuit DPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 17.88mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7201K9A3QE
Package - 7000 Series 7000 Circuit DPDT Switch Function On-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 17.88mm Illumination Type, Color 11luminated 11lumination Type, Color 11lumination Voltage (Nominal) - 11lumination Type Termination Style PC Pin Panel Cutout Dimensions - 12luminated 11ngress Protection - 15luminated 11ngress Protection - 15luminated 11ngress Protection - 15luminated 11lumination Style 11	Manufacturer	C&K
Package-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC28VActuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator TypeLocking LeverActuator Length17.88mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length 17.88mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Sushing Thread Unthreaded Ingress Protection - Epoxy Sealed Terminals	Actuator Type	Locking Lever
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	17.88mm
Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Through Hole, Right Angle
Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7201K9A3QE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7201K9A3QE Payment Methods



















7201K9A3QE Shipping Methods













If you have any question about 7201K9A3QE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com