

7201L1YZBE

7201L1YZBE Information

Heisener.com Gittar service starts they	Part Number Manufacturer Category Description Package	7201L1YZBE C&K Switches Toggle Switches SWITCH TOGGLE DPDT 0.4VA 20V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7201L1YZBE Specifications

Manufacturer Part Number 7201.1YZBE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit DPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Length 16.26mm Illumination Non-Illuminated Illumination Non-Illuminated Illumination Type, Color - Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/440 Ingress Protection - Features Epoxy Sealed Terminals		
Switches Toggle Switches Package - Series 000 Circuit DPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type 20V Illumination 16.26mm Illumination Type, Color - Illumination Voltage Nominal) - Illumination Syle Solder Lug Termination Syle Solder Lug Indend Syle Solder Lug Termination Syle Solder Lug Indend Syle Solder Lug Farent Syle Solder Lug Syle Syle Syle Syle Syle Syle Syle Syle	Manufacturer Part Number	7201L1YZBE
Togge SwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series700CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VXoltage Rating - DC20VActuator TypeStandard RoundActuator Length16.26mmIluminationNon-IluminatedIlumination Type, Color-Mouting TypeSandard RoundIlumination StyleSolder LugTermination StyleSolder LugInder Cutour DimensionsCircular - 6.35mm DialBushing Thread1/4-40Ingress Protection-FeaturesEposySealed Terminals	Category	Switches
Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread1/440Ingress Protection-FeaturesEpsy Sealed TerminalsFeaturesEpsy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent RatingOn-OnVoltage Rating - ACOvVoltage Rating - DC20VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fremination StyleStaled NountPanel Cutout DimensionsSolder LugBushing Thread1/4-40Ingress Protection-FeaturesEpsy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length16.26mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeStolder LugYennington StyleStolder LugPanel MountStolder LugIngers Protection1/4-40FeaturesEpoxy Sealed TerminalsFeaturesEpoxy Sealed Terminals	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeStoler LugPanel MountStoler LugIndex StyleStoler LugPanel Style-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeStoler LugPanel Cutour DimensionsStoler LugBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Staler Cerminals	Switch Function	On-On
Voltage Rating - DC20VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	20V
IluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Seature Seat	Actuator Length	16.26mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Seature	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7201L1YZBE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7201L1YZBE Payment Methods





If you have any question about 7201L1YZBE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com