

7201MD9V2BE

a Quote

7201MD9V2BE Information

Heisener.com	Part Number	7201MD9V2BE	
	Manufacturer	C&K	_ ∎ 2
	Category	Switches Toggle Switches	5.5
	Description	SWITCH TOGGLE DPDT 0.4VA 20V	
	Package	-	
		For the pricing/inventory/lead time, please contact	∎₊
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reques

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7201MD9V2BE Specifications

Manufacturer Part Number 7201MD9V2BE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit DPDT Switch Function On-On Curren Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Standardound Actuator Length Non-Illuminated Illumination Non-Illuminated Illumination Type, Color - Termination Style PC Pin Patel Cutout Dimensions - Ingress Protection - Ingress Protection -		
Switches Toggle Switches Package - Series 000 Circuit DPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type 20V Illumination 686min Illumination Type, Color - Illumination Voltage (Nominal) - Illumination Style - Indend Lottength - Indend Lottengto - Indend Style - Indend Styl	Manufacturer Part Number	7201MD9V2BE
Togle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Youting TypeProgen HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package.Series700CircuitDPDTSwich FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VXoltage Rating - DC30vActuator TypeStandarGaundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Voltage (Nominal)-Illumination StylePC PinTermination StylePC PinPanel Cutout Dimensions-Ilshing ThreadIltureadedIngress Protection-FeaturesSpoySealed Terminales	Category	Switches
Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Formination StylePC PinPanel Cutout Dimensions-Bushing ThreadUntreadedIngress Protection-FeaturesEpsy Sealed TerminalesFeaturesEpsy Sealed Terminales<		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Yoltage Rating - AC20VYoltage Rating - DC20VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Yoltage Rating - Standard StandardProme Ander StandardPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpsyseland StandardFeaturesEpsyseland StandardFe	Package	-
Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePringen HoleFermination Style-Bashing ThreadJuftreadedIntersection-FauresStory Sealed TerminationFeatures-<	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Hounting TypeFinough HolePanel Cutout Dimensions-Bushing ThreadUthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>	Switch Function	On-On
Voltage Rating - DC20VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminations	Voltage Rating - DC	20V
IluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoy Sealed Termination	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleYermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Seatures	Actuator Length	6.86mm
Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Termination	Illumination	Non-Illuminated
Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Through Hole
Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Features Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7201MD9V2BE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7201MD9V2BE Payment Methods





If you have any question about 7201MD9V2BE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com