

7201MY3V3BE

7201MY3V3BE Information

Heisener.com Other service dants here	Part Number Manufacturer Category Description Package	7201MY3V3BE C&K Switches Toggle Switches SWITCH TOGGLE DPDT 0.4VA 20V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7201MY3V3BE Specifications

Manufacturer Part Number 7201MY3V3BE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 700 Circuit DPDT Switch Function On-On Curren Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Length Standandund Illumination Non-Illuminated Illumination Voltage (Nominal) - Illumination Voltage (Nominal) - Illumination Style PC Pin Fermination Style Gricular 6.50mm Dia Ingress Protection - Ingress Protection -	-	
CategorySwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeSomandIlluminationSomandIllumination Type, Color-Illumination Voltage (Nominal)-Illumination SylePenel MountIndend SyleSice Actuator SyleIndend SyleCircular - 6.50mm DiaIllumination SyleCircular - 6.50mm DiaIndend SyleSice Actuator SyleIndend SyleSice Actuator SyleShaing ThreadMactuator SyleIngress Protection-FeaturesSice Syle Syle Syle Syle Syle Syle Syle Syl	Manufacturer Part Number	7201MY3V3BE
Togle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePer PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6x 0.75FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package.Series700CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VXoltage Rating - DC20VActuator TypeStandar RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Voltage (Nominal)-Illumination StylePerinFermination StyleCircular - 6.50mm DiaIndex Cutour DimensionsMis v.75Ishing Thread-Ingress Protection-FeaturesForsy Sealed Terminales	Category	Switches
Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fermination StylePanel MountPanel Cutout DimensionsGrcuar 6.50mm DiaBushing ThreadMox 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Yoltage Rating - AC20VYoltage Rating - DC20VActuator TypeStandard RoundActuator LengthS.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Yoltage Rating - StalePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadMos 2.5Ingress Protection-FeaturesEpoxy Sealed TerminalisFeaturesEpoxy Sealed Terminalis	Package	-
Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleCircular - 6.50mm DiaBashing ThreadMox 2.5IlluminationStandard StandardFaturesPanel StandardBashing ThreadMox 2.5FaturesStandard StandardFeaturesEposy Sealed Terminals	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Hounting TypePanel MountFermination StyleCircular - 6.50mm DiaBushing ThreadMox 200Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandar RoundActuator Length5.08mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleCircular - 6.50mm DiaPanel Cutour DimensionsMos 0.75Bushing Thread-Ingress ProtectionEpoxy Sealed TerminalsFeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC20VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadMos x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadMox 2.5Ingress Protection-FeaturesEpoy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	20V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6x 0.75Ingress Protection-FeaturesEpoysean Education	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Seature Seatu	Actuator Length	5.08mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6x 0.75Ingress Protection-FeaturesEpoxy Seatures	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	M6 x 0.75
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7201MY3V3BE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7201MY3V3BE Payment Methods



If you have any question about 7201MY3V3BE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com