

7201P1YCBE

7201P1YCBE Information

| Heisener.com | Part Number Manufacturer Category Description Package | 7201P1YCBE C&K Switches Toggle Switches SWITCH TOGGLE DPDT 0.4VA 20V - For the pricing/inventory/lead time, please contact | |
|--------------------|---|--|-----------------|
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7201P1YCBE Specifications

| Manufacturer Part Number 7201P1YCBE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit DPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Ial Anti-Rotation Illumination Non-Illuminated Illumination Non-Illuminated Illumination Type, Color - Termination Style PC Pin Readed Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/440 Ingress Protection - Features Epoxy Sealed Terminals | | |
|---|--------------------------------|------------------------|
| Switches Toggle Switches Package - Series 000 Circuit DPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Yoltage Rating - DC 20V Actuator Type 20V Illumination Son-Illuminated Illumination Type, Color - Illumination Type, Color - Illumination Type, Color - Illumination Type, Color - Illumination Type, Color Circular - Gasmen Call Illumination Type, Color - Illumination Type, Color - Illumination Type, Color Circular - Gasmen Call Illumination Type, Color - Illumination Type, Color Circular - Gastmen Call Illumination Type, Color Circular - Gastmen Call Illumination Type, Color Circular - Gastmen Call Illumination Type Circular - Gastmen Call Illumination Type Circular - Gastmen Call Illumination | Manufacturer Part Number | 7201P1YCBE |
| Togge SwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Manufacturer | C&K |
| Package-Series700CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VXoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length1.33mmIluminationNon-IluminatedIlumination Type, Color-Mouting TypePanel MountTermination StylePC inPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEposySealed Terminals | Category | Switches |
| Series7000CircuitDPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length1.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsGricular - 6.35mm DiaBushing Thread1/440Ingress Protection-FeaturesEpoxy Sealed Terminals | | Toggle Switches |
| CircuitDPDTSwitch FunctionOn-OnCurrent RatingOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fremination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/440Ingress Protection-FeaturesEpoxy Sealed Terminals | Package | - |
| Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Type21.33mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutour DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Series | 7000 |
| Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length1.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Circuit | DPDT |
| Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length1.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleCricular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Switch Function | On-On |
| Voltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Current Rating | 0.4VA (AC/DC) |
| Actuator TypeFlat Anti-RotationActuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Voltage Rating - AC | 20V |
| Actuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Voltage Rating - DC | 20V |
| IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Seatures | Actuator Type | Flat Anti-Rotation |
| Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination | Actuator Length | 21.33mm |
| Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Seature Seat | Illumination | Non-Illuminated |
| Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Illumination Type, Color | - |
| Termination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Illumination Voltage (Nominal) | - |
| Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Mounting Type | Panel Mount |
| Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Termination Style | PC Pin |
| Ingress Protection - Features Epoxy Sealed Terminals | Panel Cutout Dimensions | Circular - 6.35mm Dia |
| Features Epoxy Sealed Terminals | Bushing Thread | 1/4-40 |
| | Ingress Protection | - |
| Report errors? | Features | Epoxy Sealed Terminals |
| | | Report errors? |

7201P1YCBE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7201P1YCBE Payment Methods





If you have any question about 7201P1YCBE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com