

7203L2Y3ZQE

a Quote

7203L2Y3ZQE Information

Circle Deriver Landster	Part Number	7203L2Y3ZQE	
	Manufacturer		
	Category	Switches Toggle Switches	
	Description	SWITCH TOGGLE DPDT 5A 120V	. E
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Requ

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7203L2Y3ZQE Specifications

Manufacturer Part Number 7203L2Y32QE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit DPDT Switch Function On-Off-On Current Rating SA (ACDC) Voltage Rating - AC 28V Actuator Type Standard Round Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Type, Color Solder Lug Termination Style Solder Lug Panel Mount Solder Lug Ingress Protection - Features Epoxy Sealed Terminals		
Switches Toggle Switches Package - Series 7000 Circuit DPDT Switch Function On-Off-On Current Rating SA (AC/DC) Voltage Rating - AC Saver Voltage Rating - DC Saver Actuator Type Saver Actuator Length Saver Illumination Saver Illumination Type, Color - Illumination Type, Color Saver Illumination Style Saver Termination Style Saver Panel Cuotur Dimensions Saver Stating Thread Max (Saver) Stating Thread Saver	Manufacturer Part Number	7203L2Y3ZQE
Togle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-Off-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6x 0.75FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series700CircuitDPDTSwitch FunctionOn-Off-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length1.397mmIluminationNon-IluminatedIlumination Type, Color-Mouting TypeSandard RoundIlumination StyleSolder LugTermination StyleSolder LugPanel Cutout DimensionsSolder LugBushing ThreadMots NortIngress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
Series7000CircuitDPDTSwich FunctionOn-Off-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsSolder LugBushing ThreadMox 100Ingress Protection-FeaturesEpsy Seaded TerminatesFeaturesEpsy Seaded Terminates		Toggle Switches
CircuitDPDTSwitch FunctionOn-Off-OnCurrent RatingSA (AC/DC)Voltage Rating - AC100VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fremination StyleSolder LugPanel Cutout DimensionsSolder LugBushing ThreadM6 x 0.75FaturesEpsy Sealed TerminalsFeaturesEpsy Sealed Terminals	Package	-
Switch FunctionOn-Off-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandar RoundActuator Length13.97mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeSolder LugParentiation StyleSolder LugPanel MountSolder LugBushing ThreadMox 200Ingress Protection-FeaturesMox 200FeaturesEpoxy Sealed TerminalesFeaturesEpoxy Sealed TerminalesF	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length13.97mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugPanel SyleSolder LugIngers Protection-FeaturesForsylead (Statement Statement Statemen	Circuit	DPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandar RoundActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeStoler LugTermination StyleStoler LugPanel Cutour DimensionsStoler LugBushing ThreadMox 0.75Ingress ProtectionExposed Stoler Sto	Switch Function	On-Off-On
Voltage Rating - DC28VActuator TypeStandard RoundActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator TypeStandard RoundActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadMox .Ingress Protection-FeaturesEpoys Select Terminations	Voltage Rating - AC	120V
Actuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	28V
IluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Scaled Termination	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Length	13.97mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Seature Seatu	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.50mm DiaBushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing ThreadM6 x 0.75Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	M6 x 0.75
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7203L2Y3ZQE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7203L2Y3ZQE Payment Methods





If you have any question about 7203L2Y3ZQE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com