



7203L40DZQE Information

Heisener.com

Part Number 7203L40DZQE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7203L40DZQE Specifications

Manufacturer Part Number 7203L40DZQE Manufacturer C&K Category Switches Package - Series 7000 Circuit DPDT Switch Function On-Off-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Lever for Cap Actuator Length - Illumination Non-Illuminated Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLever for CapActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7203L40DZQE
Package-Series7000CircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLever for CapActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package - Series 7000 Circuit DPDT Switch Function On-Off-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Lever for Cap Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
Series 7000 Circuit DPDT Switch Function On-Off-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Lever for Cap Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		Toggle Switches
Circuit DPDT Switch Function On-Off-On Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Lever for Cap Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Package	-
Switch FunctionOn-Off-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLever for CapActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLever for CapActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeLever for CapActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Off-On
Voltage Rating - DC Actuator Type Lever for Cap Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread Ingress Protection Features 28V Lever for Cap Lever for Cap Lever for Cap Lever for Cap Lever for Cap Lever for Cap	Current Rating	5A (AC/DC)
Actuator Type Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length - Illumination Non-Illuminated Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Style Solder Lug Solder Lug Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Actuator Type	Lever for Cap
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Length	-
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7203L40DZQE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7203L40DZQE Payment Methods



















7203L40DZQE Shipping Methods













If you have any question about 7203L40DZQE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com