

# **7203MYAQE**

## 7203MYAQE Information

Contact tencer account	Part Number Manufacturer Category Description Package	7203MYAQE C&K Switches Toggle Switches SWITCH TOGGLE DPDT 5A 120V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# 7203MYAQE Specifications

Manufacturer Part Number 7203MYAQE   Manufacturer C&K   Anufacturer Switches   Category Toggle Switches   Package -   Series 7000   Circuit DPDT   Switch Function On-Off-On   Curren Rating SA (AC/DC)   Voltage Rating - AC 20V   Voltage Rating - DC Saturdat Round   Actuator Type Standard Round   Actuator Length Non-Illuminated   Illumination Non-Illuminated   Illumination Type, Color -   Illumination Voltage (Nominal) -   Actuator Length Sciellar - 6.35mm Dia   Illumination Type, Color -   Illumination Style PC Pin   Panel Cutout Dimensions Circular - 6.35mm Dia   Bushing Thread 1/4-40   Ingress Protection -   Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series7000CircuitDPDTSwitch FunctionOnOff-OnCurrent RatingSA (AC/DC)Voltage Rating - AC28VVoltage Rating - DCStandard RoundActuator TypeSommIlluminationSommIllumination Type, Color-Illumination Type, Color-Illumination SylePC PinTermination SyleCircular - A.Simm DiaIndent TypeDentIllumination SyleCircular - A.Simm DiaIndent Cutour DimensionsCircular - A.Simm DiaIndent Cutour DimensionsCircular - A.Simm DiaIndent Cutour DimensionsCircular - A.Simm DiaIndent SyleSimm DiaIndent SyleCircular - A.Simm DiaIndent SyleSing ThreadIndent SyleSing ThreadIndent SyleCircular - A.Simm DiaIndent SyleSing ThreadIndent SyleSing ThreadIn		
Toggle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-Off-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator LengthS.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel Mount, Right AnglePanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series7000CircuitDPDTSwitch FunctionOn-Off-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeSandard RoundActuator LengthSommIluminationNon-IlluminatedIlumination Voltage (Nominal)-Mouting TypePanel Mount, Right AngleTermination StyleCircular - G.Simm DiaPanel Cutout DimensionsCircular - G.Simm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
Series7000CircuitDPDTSwitch FunctionOn-Off-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator LengthS.08mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Termination StylePen Mount, Right AnglePanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-Off-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator LengthSomIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AnglePanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminales	Package	-
Switch FunctionOn-Off-OnCurrent Rating5A (AC/DC)Voltage Rating - AC100VVoltage Rating - DC28VActuator TypeSomanActuator Length5.08mmIluminationNon-IlluminatedIlumination Yupe Color-Ilumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCircular - 6.35mm DiaBushing Thread14:40Ingress Protection-FeaturesEpsy Seader Jennials	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandar RoundActuator Length5.08mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleFermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEposySeature EnglishFeaturesEposySeature English	Switch Function	On-Off-On
Voltage Rating - DC28VActuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator TypeStandard RoundActuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length5.08mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	28V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Length	5.08mm
Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount, Right Angle
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### 7203MYAQE Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 

If you have any question about 7203MYAQE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com