

7205SPYZQE

7205SPYZQE Information

Heisener.com	Part Number Manufacturer Category Description Package	7205SPYZQE C&K Switches Toggle Switches SWITCH TOGGLE DPDT 5A 120V - For the pricing/inventory/lead time, please contact	
For Reference Only	Dnly	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7205SPYZQE Specifications

Manufacturer Part Number 7205SPYZQE Manufacturer C&K Category Switches Toggle Switches Toggle Switches Package - Series 7000 Circuit DPDT Switch Function Mom-Off-Mom Current Rating SA (A/DC) Voltage Rating - AC 28V Actuator Type Anti-Rotation Actuator Length 10.67mm Illumination Non-Illuminated Illumination Type, Color - Illumination Type, Color Solder Lug Termination Style Solder Lug Panel Mount Incercation Ingress Protection - Features Epoxy Scaled Terminals		
CategorySwitchesToggle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionMon-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationIluminationNon-IlluminatedIlumination Voltage (Nominal)-Ilumination StyleSolder LugNouting TypeSolder LugPanel Cutout DimensionsCircular 6.35mm DiaBushing Thread1/440Ingress Protection-FeaturesEpoxy Seader Terminales	Manufacturer Part Number	7205SPYZQE
Toggle SwitchesPackage-Series7000CircuitDPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator LengthNon-IlluminatedIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Youting TypeSolder LugPanel Mounting TypeSolder LugIndentify StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Scaled Terminals	Manufacturer	C&K
Package-Series700CircuitDPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length1067mmIluminationNon-IlluminatedIlumination Voltage (Nominal)-Humination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread1/4-40Ingress Protection-FeaturesEposySeaturentiansFeaturesEposySeaturentians	Category	Switches
Series7000CircuitDPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Treminals		Toggle Switches
CircuitDPDTSwitch FunctionMom-Off-MomCurrent RatingSA (AC/DC)Voltage Rating - AC100VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugIndiction StyleSolder LugBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Curren Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugIngens Protection1/440FaturesEaturesFaturesEpsy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountPanel Cutour DimensionsSolder LugBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	Mom-Off-Mom
Voltage Rating - DC28VActuator TypeAnti-RotationActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator TypeAnti-RotationActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	28V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Type	Anti-Rotation
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	10.67mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7205SPYZQE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

7205SPYZQE Payment Methods





If you have any question about 7205SPYZQE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com