



7205T1PZQI Information

Heisener com

Part Number 7205T1PZQI

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 5A 120V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7205T1PZQI Specifications

Manufacturer Part Number 7205T1PZQI Manufacturer C&K Category Switches Package - Series 7000 Circuit DPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 12.37mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Epoxy Potted		
Category Switches Package - Series 7000 Circuit DPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 12.37mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Epoxy Potted	Manufacturer Part Number	7205T1PZQI
Package - 7000 Circuit DPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Lillumination Type, Color 12.37mm Illumination Type, Color - 11.91mm Dia Illumination Type Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15.32-32 Ingress Protection - Epoxy Potted	Manufacturer	C&K
Package - Series 7000 Circuit DPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 12.37mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Epoxy Potted	Category	Switches
Series 7000 Circuit DPDT Switch Function Mom-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 12.37mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Epoxy Potted		Toggle Switches
CircuitDPDTSwitch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length12.37mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Potted	Package	-
Switch FunctionMom-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length12.37mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Potted	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeAnti-RotationActuator Length12.37mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Potted	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Anti-Rotation Actuator Length 12.37mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection Features 120V 28V Anti-Rotation Non-Illumination Non-Illuminated 12.37mm Non-Illuminated 15.37mm Non-Illuminated 15.37mm Non-Illuminated 15.37mm Non-Illuminated 15/32-32 Epoxy Potted	Switch Function	Mom-Off-Mom
Voltage Rating - DC Actuator Type Anti-Rotation 12.37mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features 28V Anti-Rotation 12.37mm Non-Illumination Non-Illuminated - Solder Lug Panel Mount Solder Lug Circular - 11.91mm Dia 15/32-32 Ingress Protection Epoxy Potted	Current Rating	5A (AC/DC)
Actuator Type Anti-Rotation Actuator Length 12.37mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Epoxy Potted	Voltage Rating - AC	120V
Actuator Length 12.37mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Epoxy Potted	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Epoxy Potted	Actuator Type	Anti-Rotation
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection Features Epoxy Potted	Actuator Length	12.37mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Epoxy Potted	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesEpoxy Potted	Illumination Type, Color	-
Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Epoxy Potted	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread 15/32-32 Ingress Protection Features Circular - 11.91mm Dia 15/32-32 Epoxy Potted	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection - Features Epoxy Potted	Termination Style	Solder Lug
Ingress Protection Features Epoxy Potted	Panel Cutout Dimensions	Circular - 11.91mm Dia
Features Epoxy Potted	Bushing Thread	15/32-32
	Ingress Protection	-
Donort awars?	Features	Epoxy Potted
Report errors?		Report errors?

7205T1PZQI Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7205T1PZQI Payment Methods



















7205T1PZQI Shipping Methods













If you have any question about 7205T1PZQI, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com