



### 7207P1Y1ZGE Information

Heisener.com

Part Number 7207P1Y1ZGE

**Manufacturer** C&K **Category** Switches

Toggle Switches

**Description** SWITCH TOGGLE DPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 7207P1Y1ZGE Specifications

Manufacturer Part Number         7207P1Y1ZGE           Manufacturer         C&K           Category         Switches           Package         -           Series         7000           Circuit         DPDT           Switch Function         On-Off-Mom           Current Rating         5A (AC/DC)           Voltage Rating - AC         120V           Voltage Rating - DC         28V           Actuator Type         Flat Anti-Rotation           Actuator Length         21.33mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.35mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals           Report errors?		
CategorySwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7207P1Y1ZGE
Package - 7000  Circuit DPDT  Switch Function On-Off-Mom  Current Rating 5A (AC/DC)  Voltage Rating - AC 120V  Voltage Rating - DC 28V  Actuator Type Flat Anti-Rotation  Actuator Length 21.33mm  Illumination Type, Color - 11lumination Type, Color - 11lumination Voltage (Nominal) - 11lumination Voltage (Nominal) - 11lumination Style Solder Lug  Panel Cutout Dimensions Circular - 6.35mm Dia  Bushing Thread 1/4-40  Ingress Protection - Epoxy Sealed Terminals	Manufacturer	C&K
Package         -           Series         7000           Circuit         DPDT           Switch Function         On-Off-Mom           Current Rating         5A (AC/DC)           Voltage Rating - AC         120V           Voltage Rating - DC         28V           Actuator Type         Flat Anti-Rotation           Actuator Length         21.33mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.35mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals	Category	Switches
Series         7000           Circuit         DPDT           Switch Function         On-Off-Mom           Current Rating         5A (AC/DC)           Voltage Rating - AC         120V           Voltage Rating - DC         28V           Actuator Type         Flat Anti-Rotation           Actuator Length         21.33mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.35mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length21.33mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Off-Mom
Voltage Rating - DC  Actuator Type  Flat Anti-Rotation  Actuator Length  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Panel Cutout Dimensions  Circular - 6.35mm Dia  Bushing Thread  Ingress Protection  Features  Epoxy Sealed Terminals	Current Rating	5A (AC/DC)
Actuator Type Flat Anti-Rotation Actuator Length 21.33mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.35mm Dia  Bushing Thread 1/4-40  Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	120V
Actuator Length  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Panel Cutout Dimensions  Circular - 6.35mm Dia  Bushing Thread  Ingress Protection  Features  Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Flat Anti-Rotation
Illumination Type, Color Illumination Voltage (Nominal)  Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Length	21.33mm
Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.35mm Dia  Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.35mm Dia  Bushing Thread 1/4-40  Ingress Protection -  Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions  Circular - 6.35mm Dia  Bushing Thread  1/4-40  Ingress Protection  Features  Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

### 7207P1Y1ZGE Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 7207P1Y1ZGE Payment Methods





















### 7207P1Y1ZGE Shipping Methods













If you have any question about 7207P1Y1ZGE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com