



7207P4D9AQE Information

Heisener com

Part Number 7207P4D9AQE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7207P4D9AQE Specifications

| Manufacturer Part Number 7207P4D9AQE Manufacturer C&K Category Switches Package - Series 7000 Circuit DPDT Switch Function On-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 8.13mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals | | |
|---|--------------------------------|---------------------------|
| CategorySwitchesPackage-Series7000CircuitDPDTSwitch FunctionOn-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length8.13mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals | Manufacturer Part Number | 7207P4D9AQE |
| Package - Series 7000 Circuit DPDT Switch Function On-Off-Mom Current Rating SA (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 8.13mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Monuting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals | Manufacturer | C&K |
| Package - Series 7000 Circuit DPDT Switch Function On-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 8.13mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals | Category | Switches |
| Series 7000 Circuit DPDT Switch Function On-Off-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 8.13mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals | | Toggle Switches |
| CircuitDPDTSwitch FunctionOn-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length8.13mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals | Package | - |
| Switch FunctionOn-Off-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length8.13mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals | Series | 7000 |
| Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length8.13mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals | Circuit | DPDT |
| Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length8.13mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals | Switch Function | On-Off-Mom |
| Voltage Rating - DC Actuator Type Flat Anti-Rotation Actuator Length 8.13mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals | Current Rating | 5A (AC/DC) |
| Actuator Type Flat Anti-Rotation Actuator Length 8.13mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals | Voltage Rating - AC | 120V |
| Actuator Length 8.13mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals | Voltage Rating - DC | 28V |
| Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals | Actuator Type | Flat Anti-Rotation |
| Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals | Actuator Length | 8.13mm |
| Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals | Illumination | Non-Illuminated |
| Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals | Illumination Type, Color | - |
| Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals | Illumination Voltage (Nominal) | - |
| Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals | Mounting Type | Through Hole, Right Angle |
| Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals | Termination Style | PC Pin |
| Ingress Protection - Epoxy Sealed Terminals | Panel Cutout Dimensions | - |
| Features Epoxy Sealed Terminals | Bushing Thread | Unthreaded |
| | Ingress Protection | - |
| Report errors? | Features | Epoxy Sealed Terminals |
| | | Report errors? |

7207P4D9AQE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7207P4D9AQE Payment Methods





















7207P4D9AQE Shipping Methods













If you have any question about 7207P4D9AQE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com