



7211L2PHZBE Information

Heisener.com

Part Number 7211L2PHZBE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SP3T 0.4VA 20V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7211L2PHZBE Specifications

Manufacturer Part Number 7211L2PHZBE Manufacturer C&K Category Switches Package - Series 7000 Circuit SP3T Switch Function On-On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw			
Category Switches Package - Series 7000 Circuit SP3T Switch Function On-On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Manufacturer Part Number	7211L2PHZBE	
Package - 7000 Series 7000 Circuit SP3T Switch Function On-On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Manufacturer	C&K	
Package - Series 7000 Circuit SP3T Switch Function On-On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Category	Switches	
Series 7000 Circuit SP3T Switch Function On-On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw		Toggle Switches	
CircuitSP3TSwitch FunctionOn-On-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Package	-	
Switch FunctionOn-On-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Series	7000	
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Circuit	SP3T	
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeAnti-RotationActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Switch Function	On-On-On	
Voltage Rating - DC20VActuator TypeAnti-RotationActuator Length13.97mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Current Rating	0.4VA (AC/DC)	
Actuator Type Anti-Rotation Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Voltage Rating - AC	20V	
Actuator Length 13.97mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Voltage Rating - DC	20V	
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Actuator Type	Anti-Rotation	
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Actuator Length	13.97mm	
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination	Non-Illuminated	
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Illumination Type, Color	-	
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination Voltage (Nominal)	-	
Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Jumper needed to achieve triple throw	Mounting Type	Panel Mount	
Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Termination Style	Solder Lug	
Ingress Protection - Features Jumper needed to achieve triple throw	Panel Cutout Dimensions	Circular - 6.35mm Dia	
Features Jumper needed to achieve triple throw	Bushing Thread	1/4-40	
	Ingress Protection	-	
Report errors?	Features	Jumper needed to achieve triple throw	
			Report errors?

7211L2PHZBE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7211L2PHZBE Payment Methods



















7211L2PHZBE Shipping Methods













If you have any question about 7211L2PHZBE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com