



7213P3HZQE Information

Heisener.com

Part Number 7213P3HZQE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE SP3T 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7213P3HZQE Specifications

Manufacturer Part Number 7213P3HZQE Manufacturer C&K Category Switches Toggle Switches Package - Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	_	
Category Switches Package - Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Manufacturer Part Number	7213P3HZQE
Package - 7000 Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Manufacturer	C&K
Package - Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Category	Switches
Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw		Toggle Switches
CircuitSP3TSwitch FunctionOn-On-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Package	-
Switch FunctionOn-On-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Series	7000
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Circuit	SP3T
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread Ingress Protection Features 120V 28V 28V 28V Actuator Length Flat Anti-Rotation Non-Illumination Non-Illumination Non-Illuminated 11.43mm Non-Illuminated 11.43mm Non-Illuminated 11.43mm Non-Illuminated 11.43mm Non-Illuminated 11.440 11.440 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 11.450 1	Switch Function	On-On-Mom
Voltage Rating - DC28VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Current Rating	5A (AC/DC)
Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Voltage Rating - AC	120V
Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Actuator Type	Flat Anti-Rotation
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Actuator Length	11.43mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Jumper needed to achieve triple throw	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Termination Style	Solder Lug
Ingress Protection - Features Jumper needed to achieve triple throw	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Jumper needed to achieve triple throw	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Jumper needed to achieve triple throw
		Report errors?

7213P3HZQE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7213P3HZQE Payment Methods



















7213P3HZQE Shipping Methods













If you have any question about 7213P3HZQE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com