



7213TZGE Information

Heisener.com

For Reference Only

Part Number 7213TZGE
Manufacturer C&K
Category Switches

Toggle Switches

Description SWITCH TOGGLE SP3T 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7213TZGE Specifications

Manufacturer 7213TZGE Manufacturer C&K Category Switches Package - Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw			
CategorySwitchesPackage-Series7000CircuitSP3TSwitch FunctionOn-On-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesJumper needed to achieve triple throw	Manufacturer Part Number	7213TZGE	
Package - 7000 Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Monuting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Manufacturer	C&K	
Package - Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Category	Switches	
Series 7000 Circuit SP3T Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw		Toggle Switches	
CircuitSP3TSwitch FunctionOn-On-MomCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesJumper needed to achieve triple throw	Package	-	
Switch Function On-On-Mom Current Rating 5A (AC/DC) Voltage Rating - AC 120V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Series	7000	
Current Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesJumper needed to achieve triple throw	Circuit	SP3T	
Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length17.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 11.91mm DiaBushing Thread15/32-32Ingress Protection-FeaturesJumper needed to achieve triple throw	Switch Function	On-On-Mom	
Voltage Rating - DC Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread Ingress Protection Features Jumper needed to achieve triple throw	Current Rating	5A (AC/DC)	
Actuator Type Standard Round Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Jumper needed to achieve triple throw	Voltage Rating - AC	120V	
Actuator Length 17.45mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Voltage Rating - DC	28V	
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Actuator Type	Standard Round	
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Actuator Length	17.45mm	
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination	Non-Illuminated	
Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination Type, Color	-	
Termination Style Solder Lug Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Illumination Voltage (Nominal)	-	
Panel Cutout Dimensions Circular - 11.91mm Dia Bushing Thread 15/32-32 Ingress Protection Features Jumper needed to achieve triple throw	Mounting Type	Panel Mount	
Bushing Thread 15/32-32 Ingress Protection - Features Jumper needed to achieve triple throw	Termination Style	Solder Lug	
Ingress Protection - Features Jumper needed to achieve triple throw	Panel Cutout Dimensions	Circular - 11.91mm Dia	
Features Jumper needed to achieve triple throw	Bushing Thread	15/32-32	
	Ingress Protection	-	
Report errors?	Features	Jumper needed to achieve triple throw	
*			Report errors?

7213TZGE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7213TZGE Payment Methods



















7213TZGE Shipping Methods













If you have any question about 7213TZGE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com