



7301P3Y1ZBE Information

Heisener.com

Part Number 7301P3Y1ZBE

Manufacturer C&K **Category** Switches

Toggle Switches

Description SWITCH TOGGLE 3PDT 0.4VA 20V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









7301P3Y1ZBE Specifications

Manufacturer Part Number 7301P3Y1ZBE Manufacturer C&K Category Switches Package - Series 7000 Circuit 3PDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-Series7000Circuit3PDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	7301P3Y1ZBE
Package - Series 7000 Circuit 3PDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Manufacturer	C&K
Package - Series 7000 Circuit 3PDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
Series 7000 Circuit 3PDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 20V Voltage Rating - DC 20V Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		Toggle Switches
Circuit3PDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	3PDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeFlat Anti-RotationActuator Length11.43mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC Actuator Type Flat Anti-Rotation Actuator Length Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator Type Flat Anti-Rotation Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	20V
Actuator Length 11.43mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	20V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Flat Anti-Rotation
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	11.43mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.35mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

7301P3Y1ZBE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

7301P3Y1ZBE Payment Methods



















7301P3Y1ZBE Shipping Methods













If you have any question about 7301P3Y1ZBE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com