

## 7301SDZQI

t a Quote

### 7301SDZQI Information

| Part Number  | 7301SDZQI   |   |
|--------------|---|---|
| Manufacturer | C&K   |   |
| Category     | Switches<br>Toggle Switches   | . 20  |
| Description  | SWITCH TOGGLE 3PDT 5A 120V  | - 43a   |
| Package      | -   | - H K   |
|              | For the pricing/inventory/lead time, please contact                       |   |
|              | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com | Reques  |
|              | Manufacturer<br>Category<br>Description                                   | Toggle Switches   Description SWITCH TOGGLE 3PDT 5A 120V   Package -   For the pricing/inventory/lead time, please contact us   Website: https://www.heisener.com |

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 7301SDZQI Specifications

| Manufacturer Part Number   73018D2QI     Manufacturer   C&K     Category   Switches     Toggle Switches   Toggle Switches     Package   -     Series   7000     Circuit   3DDT     Switch Function   On-On     Current Rating   SA (AC/DC)     Voltage Rating - AC   20V     Voltage Rating - DC   28V     Actuator Length   12.45mm     Illumination   Non-Illuminated     Illumination   Non-Illuminated     Illumination Type, Color   -     Termination Style   Solder Lug     Panel Mount   Solder Lug     Index of Style   Solder Lug     Panel Cutout Dimensions   Circular - 6.35mm Dia     Bushing Thread   1/4-40     Ingress Protection   -     Features   Epoxy Potted |                                |                       |
|--|--------------------------------|-----------------------|
| CategorySwitchesPackage-Series700Circuit3PDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Volage Rating - AC28VVolage Rating - DCSaturd RoundActuator TypeStandard RoundIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage Nominally-Nouting TypeSolder LugInduning TypeSolder LugInduning TypeSolder LugInduning TypeSolder LugInduning SyleSolder LugInder Coutor DimensionsCircular - 6.55mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEposy Potted  | Manufacturer Part Number       | 7301SDZQI             |
| Toggle SwitchesPackage-Series7000Circuit3PDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mouting TypeSolder LugTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Potted   | Manufacturer                   | C&K                   |
| Package.Series7000Circuit3PDTSwitch FunctionOn-OnCurrent Rating5A (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIluminationNon-IluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mouting TypeSolder LugPanel MountSider LugIndended StreigeSider LugIndended StreigeSider LugFernination StyleCircular - 6.35mm DiaBushing Thread1/440Ingress Protection-FeaturesEpoxy Potted   | Category                       | Switches              |
| Series7000Circuit3PDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length1.245mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/440Ingress Protection-FeaturesEpoxy Potted  |                                | Toggle Switches       |
| Circuit3PDTSwitch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsSolder LugBushing Thread1/440Ingress Protection-FeaturesEpoxy Potted   | Package                        | -                     |
| Switch FunctionOn-OnCurrent RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DCSatNatActuator TypeStandard RoundActuator Length1245mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Premination StyleSolder LugPanel MountStolard RoundIndex StyleSolder LugIngers Protection-FeaturesFoxy PottedFeaturesSpory Potted  | Series                         | 7000                  |
| Current RatingSA (AC/DC)Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugPanel MountSolder LugIndex StyleSolder LugPanel Cutout DimensionsCircular 6.35mm DiaBushing Thread1/4-40Ingress ProtectionEpoxy Potted   | Circuit                        | 3PDT                  |
| Voltage Rating - AC120VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutour DimensionsI/440Bushing Thread1/440FaturesEpoy Potted  | Switch Function                | On-On                 |
| Voltage Rating - DC28VActuator TypeStandard RoundActuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Potted   | Current Rating                 | 5A (AC/DC)            |
| Actuator TypeStandard RoundActuator Length12.45nmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35nm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpox Potted  | Voltage Rating - AC            | 120V                  |
| Actuator Length12.45mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Potted  | Voltage Rating - DC            | 28V                   |
| IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Potted  | Actuator Type                  | Standard Round        |
| Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpox Potted  | Actuator Length                | 12.45mm               |
| Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Potted  | Illumination                   | Non-Illuminated       |
| Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpox Potted  | Illumination Type, Color       | -                     |
| Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Potted   | Illumination Voltage (Nominal) | -                     |
| Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Potted  | Mounting Type                  | Panel Mount           |
| Bushing Thread1/4-40Ingress Protection-FeaturesEpox Potted   | Termination Style              | Solder Lug            |
| Ingress Protection-FeaturesEpoxy Potted  | Panel Cutout Dimensions        | Circular - 6.35mm Dia |
| Features Epoxy Potted  | Bushing Thread                 | 1/4-40                |
|  | Ingress Protection             | -                     |
| Report errors?   | Features                       | Epoxy Potted          |
|  |                                | Report errors?        |

### 7301SDZQI Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# 7301SDZQI Payment Methods Image: Im

If you have any question about 7301SDZQI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com