

7301SYCKE

7301SYCKE Information

Heisener.com Ottal service softs ber	Part Number Manufacturer Category Description Package	7301SYCKE C&K Switches Toggle Switches SWITCH TOGGLE 3PDT 0.4VA 20V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



7301SYCKE Specifications

Manufacturer C&K Category Switches Package - Series 7000 Carcuit 3PDT Switch Function On-On Curren Rating 0.4VA (AC/DC) Yoltage Rating - AC 0.4VA (AC/DC) Voltage Rating - AC 0.4VA (AC/DC) Actuator Type 0404 Actuator Type Standard Round Illumination Non-Illuminated Illumination Type, Color - Illumination Type, Color - Termination Style Penineuton Indenduction Style Circular - 6.35mm Dia Instreamed Incluance - 6.35mm Dia Indenduction Style Circular - 6.35mm Dia Instreamed Incluance - 6.35mm Dia Instreamed Incluance - 6.35mm Dia Ingress Protection - Ingress Protection -		
SwitchesPackage-Series7000Circuit7000Switch Function7000Current Rating0-0Voltage Rating - AC04VA (AC/DC)Voltage Rating - DC20VActuator Type20VActuator Length10.67mmIllumination0.61lluminatedIllumination Type, Color-Munting Type9Munting Type9Panel Cutor DinensionsCircular - 6.35mm DiaIllumination StyleCircular - 6.35mm DiaPanel Cutor Dinensions1/440Rates Protection-FaturesExposed Terminals	Manufacturer Part Number	7301SYCKE
Togle SwitchesPackage-Series7000Circuit3PDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Youting TypePanel MountTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	C&K
Package-Series700Circuit3PDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Voltage Nominal)-Mouting TypePanel MountIndentify SelectionPanel MountPanel Cutour DimensionsCircular - 6.35mm DialBushing Thread14-40Ingress Protection-FeaturesEpoxy Select Terminalis	Category	Switches
Series7000Circuit3PDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-PrenePael MountTermination StylePice NamePanel Cutout DimensionsCircular 6.35mm DiaBushing Thread1/440Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
Circuit3PDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Actuator StylePanel MountTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Nonting TypePanel MountTermination StyleCircular - 6.35mm DiaBushing Thread1/4-40Inges Protection-FeaturesEpoxy Sealed Terminals	Series	7000
Current Rating0.4VA (AC/DC)Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Nonting TypePanel MountTermination StyleCircular - 6.35mm DiaBushing ThreadI/440Ingress Protection-FeaturesEpoys SeatureFeaturesEpoys SeatureFeatureEpoys Seatu	Circuit	3PDT
Voltage Rating - AC20VVoltage Rating - DC20VActuator TypeStandard RoundActuator Type10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleCricular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC20VActuator TypeStandard RoundActuator Length10.67mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeStandard RoundActuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoys Sealed Terminals	Voltage Rating - AC	20V
Actuator Length10.67mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	20V
IluminationNon-IlluminatedIlumination Type, Color-Ilumination Type, Color-Ilumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Scaled Termination	Actuator Type	Standard Round
Illumination Type, Color-Illumination Yoltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Length	10.67mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StylePC PinPanel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.35mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.35mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Depart among?	Features	Epoxy Sealed Terminals
kepon errors?		Report errors?

7301SYCKE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 7301SYCKE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com