

73725-0010BLF

73725-0010BLF Information

Heisener.com	 73725-0010BLF Amphenol FCI Connectors, Interconnects USB, DVI, HDMI Connectors USB SIDE MODUL 4 PIN LF - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



73725-0010BLF Specifications

Manufacturer Part Number73725-0010BLFManufacturerAmphenol FCICategoryConnectors, InterconnectsPackage-Package-Series73725Connector TypeUSB - ANumber of Contacts4GenderReceptacleSpecificationsUSB 2.0Mounting TypeThrough Hole, Right AngleMounting FeatureSolderFeaturesBoard Lock, Sensor ContactIngress Protection-Operating Temperature1Number of Ports1Current Rating2.5AVoltage - Rated-Manufor Cycles5.50CManufor Cycles5.50CNumber of Ports1Current Rating5.50CManufor Cycles5.50CManufor Cycles5.50CManufor Cycles5.50CManufor Cycles5.50CMating Cycles5.50C <th></th> <th></th>		
CategoryConnectors, InterconnectsUSB, DVI, HDMI ConnectorsPackage-Series73725Connector TypeUSB - ANumber of Contacts4GenderReceptacleSpecificationsUSB 2.0Mounting TypeVerticalMounting FeatureSolderFeaturesSolderIngress Protection-Operating Temperature1Quinter of Ports1Current Rating2.5AVoltage - Rated2.5AMating Cycles1500Shielding5.00Stielding <td< td=""><td>Manufacturer Part Number</td><td>73725-0010BLF</td></td<>	Manufacturer Part Number	73725-0010BLF
ValueUSB, DVI, HDMI ConnectorsPackage-Series73725Connector TypeUSB - ANumber of Contacts4GenderReceptacleSpecificationsUSB 2.0Mounting TypeThrough Hole, Right AngleMounting FeatureSolderFeaturesBoard Lock, Sensor ContactIngress Protection-Operating Temperature-55°C ~ 85°CNumber of Ports1Current Rating-Voltage - Rated-Mating Cycles1500ShieldingShielded	Manufacturer	Amphenol FCI
Package-Series73725Connector TypeUSB - ANumber of Contacts4GenderReceptacleSpecificationsUSB 2.0Mounting TypeVerticalMounting FeatureSolderFeaturesSolderIngress Protection-Number of Ports1Number of Ports1Number of Ports55°C ~ 85°CNumber of Ports5.5°C ~ 85°CNumber of Ports1Atting Cycles5.50°CShielding5.50°CSteideng5.50°C<	Category	Connectors, Interconnects
Series73725Connector TypeUSB - ANumber of Contacts4GenderReceptacleSpecificationsUSB 2.0Mounting TypeThrough Hole, Right AngleMounting FeatureVerticalTerminationSolderFeaturesBoard Lock, Sensor ContactOperating Temperature-5°C ~ 85°CNumber of Ports1Current Rating2.5AVoltage - Rated.500Shielding.500Shielding.500		USB, DVI, HDMI Connectors
Connector TypeUSB - ANumber of Contacts4GenderReceptacleSpecificationsUSB 2.0Mounting TypeThrough Hole, Right AngleMounting FeatureVerticalTerminationSolderFeaturesBoard Lock, Sensor ContactOperating Temperature-<	Package	-
Number of Contacts4GenderReceptacleGenderReceptacleSpecificationsUSB 2.0Mounting TypeThrough Hole, Right AngleMounting FeatureVerticalTerminationSolderFeaturesBoard Lock, Sensor ContactOperating Temperature-Operating Temperature55°C ~ 85°CNumber of Ports1Current Rating2.5AVoltage - Rated-Mating Cycles1500Shielding510	Series	73725
GenderReceptacleSpecificationsUSB 2.0Mounting TypeThrough Hole, Right AngleMounting FeatureVerticalTerminationSolderFeaturesBoard Lock, Sensor ContactIngress Protection-Operating Temperature55°C ~ 85°CNumber of Ports1Current Rating-Voltage - Rated-Mating Cycles1500ShieldingShielded	Connector Type	USB - A
SpecificationsUSB 2.0Mounting TypeThrough Hole, Right AngleMounting FeatureVerticalTerminationSolderFeaturesBoard Lock, Sensor ContactIngress Protection-Operating Temperature-55°C ~ 85°CNumber of Ports1Current Rating-Voltage - Rated-Mating Cycles1500ShieldingShielded	Number of Contacts	4
Nounting TypeThrough Hole, Right AngleMounting FeatureVerticalTerminationSolderFeaturesBoard Lock, Sensor ContactIngress Protection-Operating Temperature-55°C ~ 85°CNumber of Ports1Current Rating2.5AVoltage - Rated-Mating Cycles1500ShieldingShielded	Gender	Receptacle
Mounting FeatureVerticalTerminationSolderFeaturesBoard Lock, Sensor ContactIngress Protection-Operating Temperature-55°C ~ 85°CNumber of Ports1Current Rating2.5AVoltage - Rated-Mating Cycles1500ShieldingShielder	Specifications	USB 2.0
TerminationSolderFeaturesBoard Lock, Sensor ContactIngress Protection-Operating Temperature-55°C ~ 85°CNumber of Ports1Current Rating2.5AVoltage - Rated-Mating Cycles1500ShieldingShielded	Mounting Type	Through Hole, Right Angle
FeaturesBoard Lock, Sensor ContactIngress Protection-Operating Temperature-55°C ~ 85°CNumber of Ports1Current Rating2.5AVoltage - Rated-Mating Cycles1500ShieldingShielded	Mounting Feature	Vertical
Ingress Protection-Operating Temperature-55°C ~ 85°CNumber of Ports1Current Rating2.5AVoltage - Rated-Mating Cycles1500ShieldingShielded	Termination	Solder
Operating Temperature-55°C ~ 85°CNumber of Ports1Current Rating2.5AVoltage - Rated-Mating Cycles1500ShieldingShielded	Features	Board Lock, Sensor Contact
Number of Ports1Current Rating2.5AVoltage - Rated-Mating Cycles1500ShieldingShielded	Ingress Protection	-
Current Rating2.5AVoltage - Rated-Mating Cycles1500ShieldingShielded	Operating Temperature	-55°C ~ 85°C
Voltage - Rated-Mating Cycles1500ShieldingShielded	Number of Ports	1
Mating Cycles1500ShieldingShielded	Current Rating	2.5A
Shielding Shielded	Voltage - Rated	-
	Mating Cycles	1500
Report errors	Shielding	Shielded
		Report errors?

73725-0010BLF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

73725-0010BLF Payment Methods



If you have any question about 73725-0010BLF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com