


73E4R075J Information



For Reference Only

Part Number 73E4R075J

Manufacturer CTS Resistor Products

Category Resistors

Chip Resistor - Surface Mount

Description RES CURRENT SENSE THICK FILM SMD

Package 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









73E4R075J Specifications

Manufacturer Part Number73E4R075JManufacturerCTS Resistor ProductsCategoryResistorsChip Resistor - Surface MountPackage1206 (3216 Metric)Series73ExResistance75 mOhmsTolerance±5%Power (Watts)0.5W, 1/2WCompositionThick FilmFeaturesCurrent SenseTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CPackage / Case1206 (3216 Metric)Supplier Device Package1206Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.028" (0.70mm)Number of Terminations2	702 HO700 Specifications	
Category Resistors Chip Resistor - Surface Mount Package 1206 (3216 Metric) Series 73Ex Resistance 75 mOhms Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Current Sense Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Manufacturer Part Number	73E4R075J
Chip Resistor - Surface Mount Package 1206 (3216 Metric) Series 73Ex Resistance 75 mOhms Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Current Sense Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Manufacturer	CTS Resistor Products
Package 1206 (3216 Metric) Series 73Ex Resistance 75 mOhms Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Current Sense Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Category	Resistors
Series 73Ex Resistance 75 mOhms Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Current Sense Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)		Chip Resistor - Surface Mount
Resistance 75 mOhms Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Current Sense Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Package	1206 (3216 Metric)
Tolerance ±5% Power (Watts) 0.5W, 1/2W Composition Thick Film Features Current Sense Temperature Coefficient ±100ppm/°C Operating Temperature -55°C ~ 125°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Series	73Ex
Power (Watts) $0.5W$, $1/2W$ CompositionThick FilmFeaturesCurrent SenseTemperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $1206 (3216 \text{ Metric})$ Supplier Device Package 1206 Size / Dimension $0.126^{\circ}\text{L} \times 0.063^{\circ}\text{W} (3.20 \text{mm} \times 1.60 \text{mm})$ Height - Seated (Max) $0.028^{\circ} (0.70 \text{mm})$	Resistance	75 mOhms
CompositionThick FilmFeaturesCurrent SenseTemperature Coefficient $\pm 100 \text{ppm/°C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $1206 (3216 \text{ Metric})$ Supplier Device Package 1206 Size / Dimension $0.126^{\circ}\text{L} \times 0.063^{\circ}\text{W} (3.20 \text{mm} \times 1.60 \text{mm})$ Height - Seated (Max) $0.028^{\circ} (0.70 \text{mm})$	Tolerance	±5%
Features Current Sense $\pm 100 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $1206 (3216 \text{ Metric})$ Supplier Device Package 1206 Size / Dimension $0.126^{\circ}\text{L} \times 0.063^{\circ}\text{W} (3.20 \text{mm} \times 1.60 \text{mm})$ Height - Seated (Max) $0.028^{\circ} (0.70 \text{mm})$	Power (Watts)	0.5W, 1/2W
Temperature Coefficient ± 100 ppm/°C Operating Temperature -55 °C ~ 125 °C Package / Case $1206 (3216 \text{ Metric})$ Supplier Device Package 1206 Size / Dimension 0.126 " L x 0.063 " W $(3.20 \text{mm x } 1.60 \text{mm})$ Height - Seated (Max) 0.028 " (0.70mm)	Composition	Thick Film
Operating Temperature -55°C ~ 125°C Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Features	Current Sense
Package / Case 1206 (3216 Metric) Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Temperature Coefficient	±100ppm/°C
Supplier Device Package 1206 Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Operating Temperature	-55°C ~ 125°C
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) 0.028" (0.70mm)	Package / Case	1206 (3216 Metric)
Height - Seated (Max) 0.028" (0.70mm)	Supplier Device Package	1206
	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Number of Terminations 2	Height - Seated (Max)	0.028" (0.70mm)
	Number of Terminations	2
Failure Rate -	Failure Rate	-
Report errors?		Report errors?

73E4R075J Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

73E4R075J Payment Methods





















73E4R075J Shipping Methods













If you have any question about 73E4R075J, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com