



74AC86SCX_SF86755A Information



For Reference Only

Part Number 74AC86SCX_SF86755A

Manufacturer ON Semiconductor

Category Integrated Circuits (ICs)
Logic - Gates and Inverters

Description IC GATE XOR 4CH 2-INP 14SOIC **Package** 14-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









74AC86SCX_SF86755A Specifications

Manufacturer Part Number 74AC86SCX_SF86755A Manufacturer ON Semiconductor Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-SOIC (0.154", 3.90mm Width) Series 74AC Logic Type XOR (Exclusive OR) Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 6 V Current - Quiescent (Max) 2μA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.9 V ~ 1.65 V Logic Level - High 2.1 V ~ 3.85 V Max Propagation Delay @ V, Max CL 8.5ns @ 5V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount		
Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-SOIC (0.154", 3.90mm Width) Series 74AC Logic Type XOR (Exclusive OR) Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 6 V Current - Quiescent (Max) Current - Output High, Low Logic Level - Low Logic Level - High Max Propagation Delay @ V, Max CL Operating Temperature -40°C ~ 85°C Mounting Type Integrated Circuits (ICs) Logic - Gates and Inverters Logic (0.154", 3.90mm Width) 2 V ~ 6 V XOR (Exclusive OR) 4 VOR (Exclu	Manufacturer Part Number	74AC86SCX_SF86755A
PackageLogic - Gates and InvertersPackage14-SOIC (0.154", 3.90mm Width)Series74ACLogic TypeXOR (Exclusive OR)Number of Circuits4Number of Inputs2Features-Voltage - Supply2 V ~ 6 VCurrent - Quiescent (Max)2µACurrent - Output High, Low24mA, 24mALogic Level - Low0.9 V ~ 1.65 VLogic Level - High2.1 V ~ 3.85 VMax Propagation Delay @ V, Max CL8.5ns @ 5V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface Mount	Manufacturer	ON Semiconductor
Package 14-SOIC (0.154", 3.90mm Width)Series 74AC Logic TypeXOR (Exclusive OR)Number of Circuits 4 Number of Inputs 2 Features $-$ Voltage - Supply $2\text{ V} \sim 6\text{ V}$ Current - Quiescent (Max) $2\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.9\text{ V} \sim 1.65\text{ V}$ Logic Level - High $2.1\text{ V} \sim 3.85\text{ V}$ Max Propagation Delay @ V, Max CL 8.5ns @ 5V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Category	Integrated Circuits (ICs)
Series $74AC$ Logic TypeXOR (Exclusive OR)Number of Circuits 4 Number of Inputs 2 Features $-$ Voltage - Supply $2 \text{ V} \sim 6 \text{ V}$ Current - Quiescent (Max) $2\mu A$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.9 \text{ V} \sim 1.65 \text{ V}$ Logic Level - High $2.1 \text{ V} \sim 3.85 \text{ V}$ Max Propagation Delay @ V, Max CL $8.5\text{ns} \oplus 5\text{V}$, 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount		Logic - Gates and Inverters
Logic Type XOR (Exclusive OR) Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 $V \sim 6$ V Current - Quiescent (Max) 2 $V \sim 6$ V Current - Output High, Low 24 $V \sim 6$ V Logic Level - Low 0.9 $V \sim 1.65$ V Logic Level - High 2.1 $V \sim 3.85$ V Max Propagation Delay @ V, Max CL 8.5ns @ 5V, 50pF Operating Temperature -40°C ~ 85 °C Mounting Type Surface Mount	Package	14-SOIC (0.154", 3.90mm Width)
Number of Circuits4Number of Inputs2Features-Voltage - Supply $2 \text{ V} \sim 6 \text{ V}$ Current - Quiescent (Max) $2\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.9 \text{ V} \sim 1.65 \text{ V}$ Logic Level - High $2.1 \text{ V} \sim 3.85 \text{ V}$ Max Propagation Delay @ V, Max CL 8.5ns @ 5V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Series	74AC
Number of Inputs 2 Features - Voltage - Supply 2 $V \sim 6 V$ Current - Quiescent (Max) 2 μ A Current - Output High, Low 24 μ A, 24 μ A Logic Level - Low 0.9 $V \sim 1.65 V$ Logic Level - High 2.1 $V \sim 3.85 V$ Max Propagation Delay @ V, Max CL 8.5 μ s @ 5V, 50 μ F Operating Temperature -40°C $\sim 85^{\circ}$ C Mounting Type Surface Mount	Logic Type	XOR (Exclusive OR)
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Number of Circuits	4
Voltage - Supply $2\ V \sim 6\ V$ $Current - Quiescent (Max) \\ Current - Output High, Low \\ 24mA, 24mA \\ Logic Level - Low \\ 0.9\ V \sim 1.65\ V$ $Logic Level - High \\ Max\ Propagation\ Delay\ @\ V, Max\ CL \\ Max\ Propagation\ Delay\ @\ V, Max\ CL \\ Operating\ Temperature \\ Mounting\ Type \\ Surface\ Mount$	Number of Inputs	2
Current - Quiescent (Max) $2\mu A$ Current - Output High, Low $24mA, 24mA$ Logic Level - Low $0.9 \text{ V} \sim 1.65 \text{ V}$ Logic Level - High $2.1 \text{ V} \sim 3.85 \text{ V}$ Max Propagation Delay @ V, Max CL $8.5ns \otimes 5V, 50pF$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type $Surface Mount$	Features	-
Current - Output High, Low 24mA , 24mA Logic Level - Low $0.9 \text{ V} \sim 1.65 \text{ V}$ Logic Level - High $2.1 \text{ V} \sim 3.85 \text{ V}$ Max Propagation Delay @ V, Max CL 8.5ns @ 5V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Voltage - Supply	2 V ~ 6 V
Logic Level - Low $0.9 \text{ V} \sim 1.65 \text{ V}$ Logic Level - High $2.1 \text{ V} \sim 3.85 \text{ V}$ Max Propagation Delay @ V, Max CL $8.5 \text{ns} \otimes 5 \text{V}$, 50pF Operating Temperature $-40 ^{\circ}\text{C} \sim 85 ^{\circ}\text{C}$ Mounting TypeSurface Mount	Current - Quiescent (Max)	2μΑ
Logic Level - High2.1 V ~ 3.85 VMax Propagation Delay @ V, Max CL8.5ns @ 5V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface Mount	Current - Output High, Low	24mA, 24mA
Max Propagation Delay @ V, Max CL8.5ns @ 5V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface Mount	Logic Level - Low	0.9 V ~ 1.65 V
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Logic Level - High	2.1 V ~ 3.85 V
Mounting Type Surface Mount	Max Propagation Delay @ V, Max CL	8.5ns @ 5V, 50pF
	Operating Temperature	-40°C ~ 85°C
	Mounting Type	Surface Mount
Supplier Device Package 14-SOIC	Supplier Device Package	14-SOIC
Package / Case 14-SOIC (0.154", 3.90mm Width)	Package / Case	14-SOIC (0.154", 3.90mm Width)
Report errors?		Report errors?

74AC86SCX_SF86755A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

74AC86SCX_SF86755A Payment Methods



















74AC86SCX_SF86755A Shipping Methods













If you have any question about 74AC86SCX_SF86755A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com