



74ACT11000DE4 Information



For Reference Only

Part Number 74ACT11000DE4

Manufacturer Texas Instruments

Category Integrated Circuits (ICs)
Logic - Gates and Inverters

Description IC GATE NAND 4CH 2-INP 16-SOIC **Package** 16-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









74ACT11000DE4 Specifications

Manufacturer Part Number 74ACT11000DE4 Manufacturer Texas Instruments Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 16-SOIC (0.154", 3.90mm Width) Series 74ACT Logic Type NAND Gate Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 4.5 V ~ 5.5 V Current - Quiescent (Max) 4μA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 10.9ns @ 5V, 50pF		
CategoryIntegrated Circuits (ICs)Logic - Gates and InvertersPackage $16\text{-SOIC } (0.154^{"}, 3.90 \text{mm Width})$ Series 74ACT Logic TypeNAND GateNumber of Circuits 4 Number of Inputs 2 Features-Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Current - Quiescent (Max) $4\mu\text{A}$ Current - Output High, Low $24\text{mA}, 24\text{mA}$ Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 10.9ns @ 5V, 50pF	Manufacturer Part Number	74ACT11000DE4
Logic - Gates and InvertersPackage16-SOIC (0.154", 3.90mm Width)Series74ACTLogic TypeNAND GateNumber of Circuits4Number of Inputs2Features-Voltage - Supply4.5 V ~ 5.5 VCurrent - Quiescent (Max)4μACurrent - Output High, Low24mA, 24mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL10.9ns @ 5V, 50pF	Manufacturer	Texas Instruments
Package 16-SOIC (0.154", 3.90mm Width) Series 74ACT Logic Type NAND Gate Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 4.5 V ~ 5.5 V Current - Quiescent (Max) 4μA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 10.9ns @ 5V, 50pF	Category	Integrated Circuits (ICs)
Series 74ACT Logic Type NAND Gate Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 4.5 V ~ 5.5 V Current - Quiescent (Max) 4μA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 10.9ns @ 5V, 50pF		Logic - Gates and Inverters
Logic TypeNAND GateNumber of Circuits4Number of Inputs2Features-Voltage - Supply4.5 V ~ 5.5 VCurrent - Quiescent (Max)4μACurrent - Output High, Low24mA, 24mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL10.9ns @ 5V, 50pF	Package	16-SOIC (0.154", 3.90mm Width)
Number of Circuits4Number of Inputs2Features-Voltage - Supply4.5 V ~ 5.5 VCurrent - Quiescent (Max)4μACurrent - Output High, Low24mA, 24mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL10.9ns @ 5V, 50pF	Series	74ACT
Number of Inputs2Features-Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Current - Quiescent (Max) $4\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 10.9ns @ 5V , 50pF	Logic Type	NAND Gate
Features-Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Current - Quiescent (Max) $4\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 10.9ns @ 5V , 50pF	Number of Circuits	4
Voltage - Supply $4.5 \text{ V} \sim 5.5 \text{ V}$ Current - Quiescent (Max) $4\mu\text{A}$ Current - Output High, Low $24\text{mA}, 24\text{mA}$ Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL $10.9\text{ns @ 5V}, 50\text{pF}$	Number of Inputs	2
Current - Quiescent (Max)4μACurrent - Output High, Low24mA, 24mALogic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL10.9ns @ 5V, 50pF	Features	-
Current - Output High, Low 24mA, 24mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 10.9ns @ 5V, 50pF	Voltage - Supply	4.5 V ~ 5.5 V
Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 10.9ns @ 5V, 50pF	Current - Quiescent (Max)	$4\mu A$
Logic Level - High 2V Max Propagation Delay @ V, Max CL 10.9ns @ 5V, 50pF	Current - Output High, Low	24mA, 24mA
Max Propagation Delay @ V, Max CL 10.9ns @ 5V, 50pF	Logic Level - Low	0.8V
	Logic Level - High	2V
	Max Propagation Delay @ V, Max CL	10.9ns @ 5V, 50pF
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Operating Temperature	-40°C ~ 85°C
Mounting Type Surface Mount	Mounting Type	Surface Mount
Supplier Device Package 16-SOIC	Supplier Device Package	16-SOIC
Package / Case 16-SOIC (0.154", 3.90mm Width)	Package / Case	16-SOIC (0.154", 3.90mm Width)
Report errors?		Report errors?

74ACT11000DE4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

74ACT11000DE4 Payment Methods



















74ACT11000DE4 Shipping Methods













If you have any question about 74ACT11000DE4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com