

Heisener.com

74H-4 Information

Part Number 74H-4
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionFUSE AT&T COLUMBUSPackageCartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









74H-4 Specifications

Manufacturer Part Number 74H-4 Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cartridge, Non-Standard Series 74 Fuse Type Cartridge Current Rating 4A Voltage Rating - AC - Voltage Rating - DC 60V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm) Report errors?		
CategoryCircuit ProtectionPackageCartridge, Non-StandardSeries74Fuse TypeCartridgeCurrent Rating4AVoltage Rating - AC-Voltage Rating - DC60VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Manufacturer Part Number	74H-4
PackageCartridge, Non-StandardSeries74Fuse TypeCartridgeCurrent Rating4AVoltage Rating - AC-Voltage Rating - DC60VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Manufacturer	Eaton
Package Cartridge, Non-Standard Series 74 Fuse Type Cartridge Current Rating 4A Voltage Rating - AC - Voltage Rating - DC 60V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Category	Circuit Protection
Series74Fuse TypeCartridgeCurrent Rating4AVoltage Rating - AC-Voltage Rating - DC60VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.281" Dia x 1.250" L (7.14mm x 31.75mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating4AVoltage Rating - AC-Voltage Rating - DC60VResponse TimeFastApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC Voltage Rating - DC 60V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 4A A A A A A A A A A A A A	Series	74
Voltage Rating - AC Voltage Rating - DC 60V Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Cantridge, Non-Standard Size / Dimension - COV 60V - CBV - CBV - CE, UR - Cartridge, Non-Standard 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 60V 60V 60V 60V 60V 60V 60V 60	Current Rating	4A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Castridge, Non-Standard Size / Dimension Fast Electrical, Industrial - CE, UR - Holder - CE, UR - Cartridge, Non-Standard 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Voltage Rating - AC	-
Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Voltage Rating - DC	60V
Features - Class - CE, UR Approvals CE, UR Operating Temperature - Estadous Capacity @ Rated Voltage - Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Response Time	Fast
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage - Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Applications	Electrical, Industrial
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, UR Cartridge, Value (1) CE, UR (2) Cartridge, Value (3) Cartridge, Value (4) Cartridge, Value (5) Cartridge, Value (6) Cartridge, Value (7) Cartridge, Value Cartridge, Value	Features	-
Operating Temperature - Grant Capacity @ Rated Voltage - Holder Holder - Holder Cartridge, Non-Standard Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Class	-
Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Approvals	CE, UR
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension 0.281" Dia x 1.250" L (7.14mm x 31.75mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.281" Dia x 1.250" L (7.14mm x 31.75mm)
		Report errors?

74H-4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

74H-4 Payment Methods



















74H-4 Shipping Methods













If you have any question about 74H-4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com