



74LCX08MTC Information



For Reference Only

Part Number 74LCX08MTC

Manufacturer ON Semiconductor

Category Integrated Circuits (ICs)
Logic - Gates and Inverters

Description IC GATE AND 4CH 2-INP 14TSSOP **Package** 14-TSSOP (0.173", 4.40mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









74LCX08MTC Specifications

Manufacturer Part Number 74LCX08MTC Manufacturer ON Semiconductor Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-TSSOP (0.173", 4.40mm Width) Series 74LCX Logic Type AND Gate Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 3.6 V Current - Quiescent (Max) 10μA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.7 V ~ 0.8 V Logic Level - High 1.7 V ~ 2 V Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP Package / Case 14-TSSOP (0.173", 4.40mm Width)		
CategoryIntegrated Circuits (ICs)Package 14 -TSSOP (0.173 ", 4.40 mm Width)Series 74 LCXLogic TypeAND GateNumber of Circuits 4 Number of Inputs 2 Features $-$ Voltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 5.5ns @ 3.3 V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP	Manufacturer Part Number	74LCX08MTC
PackageLogic - Gates and InvertersPackage14-TSSOP (0.173", 4.40mm Width)Series74LCXLogic TypeAND GateNumber of Circuits4Number of Inputs2Features-Voltage - Supply2 V ~ 3.6 VCurrent - Quiescent (Max) 10μ ACurrent - Output High, Low $24m$ A, $24m$ ALogic Level - Low $0.7 V ~ 0.8 V$ Logic Level - High $1.7 V ~ 2 V$ Max Propagation Delay @ V, Max CL $5.5ns$ @ $3.3V$, $50p$ FOperating Temperature -40° C ~ 85° CMounting TypeSurface MountSupplier Device Package $14-TSSOP$	Manufacturer	ON Semiconductor
Package 14-TSSOP (0.173", 4.40mm Width)Series 74LCX Logic TypeAND GateNumber of Circuits 4 Number of Inputs 2 Features-Voltage - Supply $2\text{ V} \sim 3.6\text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7\text{ V} \sim 0.8\text{ V}$ Logic Level - High $1.7\text{ V} \sim 2\text{ V}$ Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP	Category	Integrated Circuits (ICs)
Series 74LCX Logic Type AND Gate Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 3.6 V Current - Quiescent (Max) 10μA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.7 V ~ 0.8 V Logic Level - High 1.7 V ~ 2 V Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP		Logic - Gates and Inverters
Logic TypeAND GateNumber of Circuits4Number of Inputs2Features-Voltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP	Package	14-TSSOP (0.173", 4.40mm Width)
Number of Circuits4Number of Inputs2Features-Voltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP	Series	74LCX
Number of Inputs2Features-Voltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP	Logic Type	AND Gate
Features $ \begin{array}{ccccccccccccccccccccccccccccccccccc$	Number of Circuits	4
Voltage - Supply $2\ V \sim 3.6\ V$ $Current - Quiescent (Max) 10\mu A$ $Current - Output High, Low 24mA, 24mA$ $Logic Level - Low 0.7\ V \sim 0.8\ V$ $Logic Level - High 1.7\ V \sim 2\ V$ $Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V, 50pF$ $Operating Temperature -40^{\circ}C \sim 85^{\circ}C$ $Mounting Type Surface Mount$ $Supplier Device Package 14-TSSOP$	Number of Inputs	2
Current - Quiescent (Max) $10\mu A$ Current - Output High, Low $24mA, 24mA$ Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL $5.5ns @ 3.3V, 50pF$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type $Surface Mount$ Supplier Device Package $14-TSSOP$	Features	-
Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP	Voltage - Supply	2 V ~ 3.6 V
Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountSupplier Device Package 14-TSSOP	Current - Quiescent (Max)	10μΑ
Logic Level - High 1.7 V ~ 2 V Max Propagation Delay @ V, Max CL 5.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP	Current - Output High, Low	24mA, 24mA
Max Propagation Delay @ V, Max CL5.5ns @ 3.3V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface MountSupplier Device Package14-TSSOP	Logic Level - Low	0.7 V ~ 0.8 V
Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP	Logic Level - High	1.7 V ~ 2 V
Mounting Type Surface Mount Supplier Device Package 14-TSSOP	Max Propagation Delay @ V, Max CL	5.5ns @ 3.3V, 50pF
Supplier Device Package 14-TSSOP	Operating Temperature	-40°C ~ 85°C
	Mounting Type	Surface Mount
Package / Case 14-TSSOP (0.173", 4.40mm Width)	Supplier Device Package	14-TSSOP
	Package / Case	14-TSSOP (0.173", 4.40mm Width)
Report errors?		Report errors?

74LCX08MTC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

74LCX08MTC Payment Methods





















74LCX08MTC Shipping Methods













If you have any question about 74LCX08MTC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com