



74LCX86MTC Information



For Reference Only

Part Number 74LCX86MTC

Manufacturer Fairchild/ON Semiconductor

Category Integrated Circuits (ICs)
Logic - Gates and Inverters

Description IC GATE XOR 4CH 2-INP 14-TSSOP **Package** 14-TSSOP (0.173", 4.40mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









74LCX86MTC Specifications

Manufacturer Part Number 74LCX86MTC Manufacturer Fairchild/ON Semiconductor Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-TSSOP (0.173", 4.40mm Width) Series 74LCX Logic Type XOR (Exclusive OR) Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 3.6 V Current - Quiescent (Max) 10μA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.7 V ~ 0.8 V Logic Level - High 1.7 V ~ 2 V Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-TSSOP		
Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-TSSOP (0.173", 4.40mm Width) Series 74LCX Logic Type XOR (Exclusive OR) Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 3.6 V Current - Quiescent (Max) 10μA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.7 V ~ 0.8 V Logic Level - High 1.7 V ~ 2 V Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Manufacturer Part Number	74LCX86MTC
$\begin{array}{c} \text{Logic - Gates and Inverters} \\ \text{Package} \\ \text{Package} \\ \text{Series} \\ \text{74LCX} \\ \text{Logic Type} \\ \text{XOR (Exclusive OR)} \\ \text{Number of Circuits} \\ \text{Number of Inputs} \\ \text{2} \\ \text{Features} \\ \text{Voltage - Supply} \\ \text{Current - Quiescent (Max)} \\ \text{Current - Output High, Low} \\ \text{Logic Level - Low} \\ \text{Logic Level - High} \\ \text{Max Propagation Delay @ V, Max CL} \\ \text{Operating Temperature} \\ \text{Mounting Type} \\ \text{Surface Mount} \\ \text{Surface Mount} \\ \text{Voltage - Gates and Inverters} \\ \text{14-TSSOP (0.173", 4.40mm Width)} \\ \text{34-Auxon} \\ \text{40-CX} \\ $	Manufacturer	Fairchild/ON Semiconductor
Package14-TSSOP (0.173", 4.40mm Width)Series74LCXLogic TypeXOR (Exclusive OR)Number of Circuits4Number of Inputs2Features-Voltage - Supply2 V ~ 3.6 VCurrent - Quiescent (Max) $10\mu A$ Current - Output High, Low $24mA$, $24mA$ Logic Level - Low $0.7 V ~ 0.8 V$ Logic Level - High $1.7 V ~ 2 V$ Max Propagation Delay @ V, Max CL $6.5ns @ 3.3V$, $50pF$ Operating Temperature -40 °C ~ 85 °CMounting TypeSurface Mount	Category	Integrated Circuits (ICs)
Series $74LCX$ Logic TypeXOR (Exclusive OR)Number of Circuits4Number of Inputs2Features-Voltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount		Logic - Gates and Inverters
Logic Type XOR (Exclusive OR) Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 $V \sim 3.6 V$ Current - Quiescent (Max) 10 $V \sim 0.8 V$ Logic Level - Low 0.7 $V \sim 0.8 V$ Logic Level - High 1.7 $V \sim 2 V$ Max Propagation Delay @ $V \sim 0.8 V$ Operating Temperature -40°C ~ 85 °C Mounting Type Surface Mount	Package	14-TSSOP (0.173", 4.40mm Width)
Number of Circuits4Number of Inputs2Features-Voltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Series	74LCX
Number of Inputs 2 Features - Voltage - Supply 2 $V \sim 3.6 V$ Current - Quiescent (Max) 10 μ A Current - Output High, Low 24mA, 24mA Logic Level - Low 0.7 $V \sim 0.8 V$ Logic Level - High 1.7 $V \sim 2 V$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85 °C Mounting Type Surface Mount	Logic Type	XOR (Exclusive OR)
Features - Voltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Number of Circuits	4
Voltage - Supply $2\ V \sim 3.6\ V$ Current - Quiescent (Max) $10\mu A$ Current - Output High, Low $24mA, 24mA$ Logic Level - Low $0.7\ V \sim 0.8\ V$ Logic Level - High $1.7\ V \sim 2\ V$ Max Propagation Delay @ V, Max CL $6.5ns\ @\ 3.3V, 50pF$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type $Surface\ Mount$	Number of Inputs	2
Current - Quiescent (Max) $10\mu A$ Current - Output High, Low $24mA, 24mA$ Logic Level - Low $0.7 \ V \sim 0.8 \ V$ Logic Level - High $1.7 \ V \sim 2 \ V$ Max Propagation Delay @ V, Max CL $6.5ns \ @ \ 3.3V, 50pF$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type $Surface \ Mount$	Features	-
Current - Output High, Low 24mA , 24mA Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Voltage - Supply	2 V ~ 3.6 V
Logic Level - Low $0.7 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40 ^{\circ}\text{C} \sim 85 ^{\circ}\text{C}$ Mounting TypeSurface Mount	Current - Quiescent (Max)	10μΑ
Logic Level - High $1.7 \text{ V} \sim 2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40 ^{\circ}\text{C} \sim 85 ^{\circ}\text{C}$ Mounting TypeSurface Mount	Current - Output High, Low	24mA, 24mA
Max Propagation Delay @ V, Max CL6.5ns @ 3.3V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface Mount	Logic Level - Low	0.7 V ~ 0.8 V
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Logic Level - High	1.7 V ~ 2 V
Mounting Type Surface Mount	Max Propagation Delay @ V, Max CL	6.5ns @ 3.3V, 50pF
	Operating Temperature	-40°C ~ 85°C
Supplier Device Package 14-TSSOP	Mounting Type	Surface Mount
	Supplier Device Package	14-TSSOP
Package / Case 14-TSSOP (0.173", 4.40mm Width)	Package / Case	14-TSSOP (0.173", 4.40mm Width)
Report errors?		Report errors?

74LCX86MTC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

74LCX86MTC Payment Methods





















74LCX86MTC Shipping Methods













If you have any question about 74LCX86MTC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com