

74LCXH16245TTR

74LCXH16245TTR Information

Por Sintener.com	 74LCXH16245TTR STMicroelectronics Integrated Circuits (ICs) Logic - Buffers, Drivers, Receivers, Transceivers IC BUS TXRX 16BIT LV 48-TSSOP 48-TFSOP (0.240", 6.10mm Width) For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



74LCXH16245TTR Specifications

ManufacturerSTMicroelectronicsCategoryIntegrated Circuits (ICs)Logic - Buffers, Drivers, Receivers, TransceiversPackage48-TFSOP (0.240", 6.10mm Width)Series74LCXHLogic TypeTransceiver, Non-InvertingNumber of Elements2Number of Bits per Element8Input Type-Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)		
CategoryIntegrated Circuits (ICs) Logic - Buffers, Drivers, Receivers, TransceiversPackage48-TFSOP (0.240", 6.10mm Width)Series74LCXHLogic TypeTransceiver, Non-InvertingNumber of Elements2Number of Bits per Element8Input Type-Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Manufacturer Part Number	74LCXH16245TTR
Logic - Buffers, Drivers, Receivers, TransceiversPackage48-TFSOP (0.240", 6.10mm Width)Series74LCXHLogic TypeTransceiver, Non-InvertingNumber of Elements2Number of Bits per Element8Input Type-Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Manufacturer	STMicroelectronics
Package48-TFSOP (0.240", 6.10mm Width)Series74LCXHLogic TypeTransceiver, Non-InvertingNumber of Elements2Number of Bits per Element8Input Type-Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating TemperatureSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)	Category	Integrated Circuits (ICs)
Series74LCXHLogic TypeTransceiver, Non-InvertingNumber of Elements2Number of Bits per Element8Input Type-Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP		Logic - Buffers, Drivers, Receivers, Transceivers
Logic TypeTransceiver, Non-InvertingNumber of Elements2Number of Bits per Element8Input Type-Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)	Package	48-TFSOP (0.240", 6.10mm Width)
Number of Elements2Number of Bits per Element8Input Type-Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Series	74LCXH
Number of Bits per Element8Input Type-Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Logic Type	Transceiver, Non-Inverting
Input Type-Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Number of Elements	2
Output TypePush-PullCurrent - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Number of Bits per Element	8
Current - Output High, Low24mA, 24mAVoltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Input Type	-
Voltage - Supply2 V ~ 3.6 VOperating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Output Type	Push-Pull
Operating Temperature-55°C ~ 125°C (TA)Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Current - Output High, Low	24mA, 24mA
Mounting TypeSurface MountPackage / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Voltage - Supply	2 V ~ 3.6 V
Package / Case48-TFSOP (0.240", 6.10mm Width)Supplier Device Package48-TSSOP	Operating Temperature	-55°C ~ 125°C (TA)
Supplier Device Package 48-TSSOP	Mounting Type	Surface Mount
	Package / Case	48-TFSOP (0.240", 6.10mm Width)
Report errors?	Supplier Device Package	48-TSSOP
		Report errors?

74LCXH16245TTR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

74LCXH16245TTR Payment Methods





If you have any question about 74LCXH16245TTR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com