

74LVT10D,118 Information



For Reference Only

Part Number 74LVT10D,118

Manufacturer NXP

Category Integrated Circuits (ICs)

Logic - Gates and Inverters

Description IC GATE NAND 3CH 3-INP 14-SO **Package** 14-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









74LVT10D,118 Specifications

Manufacturer 74LVT10D,118 Manufacturer NXP Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-SOIC (0.154", 3.90mm Width) Series 74LVT Logic Type NAND Gate Number of Circuits 3 Number of Inputs 3 Features - Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) - Current - Output High, Low 20mA, 32mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 3.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SOIC (0.154", 3.90mm Width)		
Category Integrated Circuits (ICs) Package 14-SOIC (0.154", 3.90mm Width) Series 74LVT Logic Type NAND Gate Number of Circuits 3 Number of Inputs 3 Features - Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) - Current - Output High, Low 20mA, 32mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 3.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SOIC (0.154", 3.90mm Width)	Manufacturer Part Number	74LVT10D,118
Package 14-SOIC (0.154", 3.90mm Width) Series 74LVT Logic Type NAND Gate Number of Circuits 3 Number of Inputs 3 Features - Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) - Current - Output High, Low 20mA, 32mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 3.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SO Package / Case 14-SOIC (0.154", 3.90mm Width)	Manufacturer	NXP
Package 14-SOIC (0.154", 3.90mm Width) Series 74LVT Logic Type NAND Gate Number of Circuits 3 Number of Inputs 3 Features - Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) - Current - Output High, Low 20mA, 32mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 3.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SO Package / Case 14-SOIC (0.154", 3.90mm Width)	Category	Integrated Circuits (ICs)
Series 74LVT Logic Type NAND Gate Number of Circuits 3 Number of Inputs 3 Features - Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) - Current - Output High, Low 20mA, 32mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 3.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SO Package / Case 14-SOIC (0.154", 3.90mm Width)		Logic - Gates and Inverters
Logic Type NAND Gate Number of Circuits 3 Number of Inputs 3 Features - Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) - Current - Output High, Low 20mA, 32mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 3.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package Package / Case 14-SOIC (0.154", 3.90mm Width)	Package	14-SOIC (0.154", 3.90mm Width)
Number of Circuits Number of Inputs Features Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) Current - Output High, Low 20mA, 32mA Logic Level - Low Logic Level - High 2V Max Propagation Delay @ V, Max CL Operating Temperature 40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package Package / Case 3 3 3 3 3 3 4 5 6 7 7 8 8 9 8 9 8 9 8 9 8 9 8 9 9	Series	74LVT
Number of Inputs Features Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) Current - Output High, Low 20mA, 32mA Logic Level - Low Logic Level - High 2V Max Propagation Delay @ V, Max CL Operating Temperature Mounting Type Surface Mount Supplier Device Package Package / Case 3 3 3 4 4 5 7 7 8 7 8 7 8 7 8 7 8 7 8 8	Logic Type	NAND Gate
Features - Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) - Current - Output High, Low 20mA, 32mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL 3.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SOIC (0.154", 3.90mm Width)	Number of Circuits	3
Voltage - Supply 2.7 V ~ 3.6 V Current - Quiescent (Max) - Current - Output High, Low 20mA, 32mA Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SO Package / Case 14-SOIC (0.154", 3.90mm Width)	Number of Inputs	3
Current - Quiescent (Max) Current - Output High, Low Logic Level - Low Logic Level - High 2V Max Propagation Delay @ V, Max CL Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SO Package / Case	Features	-
Current - Output High, Low Logic Level - Low 0.8V Logic Level - High 2V Max Propagation Delay @ V, Max CL Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SOIC (0.154", 3.90mm Width)	Voltage - Supply	2.7 V ~ 3.6 V
Logic Level - Low0.8VLogic Level - High2VMax Propagation Delay @ V, Max CL3.8ns @ 3.3V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface MountSupplier Device Package14-SOPackage / Case14-SOIC (0.154", 3.90mm Width)	Current - Quiescent (Max)	-
Logic Level - High 2V Max Propagation Delay @ V, Max CL 3.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SO Package / Case 14-SOIC (0.154", 3.90mm Width)	Current - Output High, Low	20mA, 32mA
Max Propagation Delay @ V, Max CL 3.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SO Package / Case 14-SOIC (0.154", 3.90mm Width)	Logic Level - Low	0.8V
Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SO Package / Case 14-SOIC (0.154", 3.90mm Width)	Logic Level - High	2V
Mounting Type Surface Mount Supplier Device Package 14-SO Package / Case 14-SOIC (0.154", 3.90mm Width)	Max Propagation Delay @ V, Max CL	3.8ns @ 3.3V, 50pF
Supplier Device Package 14-SO Package / Case 14-SOIC (0.154", 3.90mm Width)	Operating Temperature	-40°C ~ 85°C
Package / Case 14-SOIC (0.154", 3.90mm Width)	Mounting Type	Surface Mount
	Supplier Device Package	14-SO
Poport arrays	Package / Case	14-SOIC (0.154", 3.90mm Width)
Report errors?		Report errors?

74LVT10D,118 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

74LVT10D,118 Payment Methods





















74LVT10D,118 Shipping Methods













If you have any question about 74LVT10D,118, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com