

74LVX86SJ Information

w/w.heisener.cym

For Reference Only

Part Number 74LVX86SJ

Manufacturer Fairchild/ON Semiconductor

Category Integrated Circuits (ICs)
Logic - Gates and Inverters

Description IC GATE XOR 4CH 2-INP 14-SOIC **Package** 14-SOIC (0.209", 5.30mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









74LVX86SJ Specifications

Manufacturer Part Number 74LVX86SJ Manufacturer Fairchild/ON Semiconductor Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-SOIC (0.209", 5.30mm Width) Series 74LVX Logic Type XOR (Exclusive OR) Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 V ~ 3.6 V Current - Quiescent (Max) 2μA Current - Output High, Low 4mA, 4mA Logic Level - Low 0.5 V ~ 0.8 V Logic Level - High 1.5 V ~ 2.4 V Max Propagation Delay @ V, Max CL 12.8ns @ 3.3V, 50pF Operating Temperature 40°C ~ 85°C Mounting Type Surface Mount Supplier Device Package 14-SOIC		
CategoryIntegrated Circuits (ICs)Package 14-SOIC ($0.209^{\circ\prime\prime}$, 5.30mm Width)Series 74LVX Logic TypeXOR (Exclusive OR)Number of Circuits 4 Number of Inputs 2 Features $-$ Voltage - Supply $2\text{ V} \sim 3.6\text{ V}$ Current - Quiescent (Max) $2\mu\text{A}$ Current - Output High, Low 4mA , 4mA Logic Level - Low $0.5\text{ V} \sim 0.8\text{ V}$ Logic Level - High $1.5\text{ V} \sim 2.4\text{ V}$ Max Propagation Delay @ V, Max CL 12.8ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Manufacturer Part Number	74LVX86SJ
$\begin{array}{c} Logic - Gates \ and \ Inverters \\ \\ Package \\ Series \\ 74LVX \\ Logic Type \\ XOR \ (Exclusive \ OR) \\ \\ Number of Circuits \\ \\ Number of Inputs \\ 2 \\ Features \\ \\ Voltage - Supply \\ 2 \ V \sim 3.6 \ V \\ \\ Current - Quiescent \ (Max) \\ Current - Output \ High, Low \\ Logic \ Level - Low \\ Logic \ Level - High \\ Max \ Propagation \ Delay \ V, \ Max \ CL \\ Operating \ Temperature \\ Operating \ Temperature \\ Mounting \ Type \\ \\ \\ Surface \ Mount \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	Manufacturer	Fairchild/ON Semiconductor
Package14-SOIC (0.209", 5.30mm Width)Series $74LVX$ Logic TypeXOR (Exclusive OR)Number of Circuits4Number of Inputs2Features-Voltage - Supply $2 V \sim 3.6 V$ Current - Quiescent (Max) $2\mu A$ Current - Output High, Low $4mA$, $4mA$ Logic Level - Low $0.5 V \sim 0.8 V$ Logic Level - High $1.5 V \sim 2.4 V$ Max Propagation Delay @ V, Max CL $12.8ns @ 3.3V$, $50pF$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting TypeSurface Mount	Category	Integrated Circuits (ICs)
Series $74LVX$ Logic TypeXOR (Exclusive OR)Number of Circuits 4 Number of Inputs 2 Features-Voltage - Supply $2 V \sim 3.6 V$ Current - Quiescent (Max) $2\mu A$ Current - Output High, Low $4mA$, $4mA$ Logic Level - Low $0.5 V \sim 0.8 V$ Logic Level - High $1.5 V \sim 2.4 V$ Max Propagation Delay @ V, Max CL $12.8ns @ 3.3V$, $50pF$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting TypeSurface Mount		Logic - Gates and Inverters
Logic Type XOR (Exclusive OR) Number of Circuits 4 Number of Inputs 2 Features - Voltage - Supply 2 $V \sim 3.6 V$ Current - Quiescent (Max) 2 μ A Current - Output High, Low 4 μ A, 4 μ A Logic Level - Low 0.5 $V \sim 0.8 V$ Logic Level - High 1.5 $V \sim 2.4 V$ Max Propagation Delay @ V, Max CL 12.8ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85 °C Mounting Type Surface Mount	Package	14-SOIC (0.209", 5.30mm Width)
Number of Circuits4Number of Inputs2Features-Voltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $2\mu\text{A}$ Current - Output High, Low 4mA , 4mA Logic Level - Low $0.5 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.5 \text{ V} \sim 2.4 \text{ V}$ Max Propagation Delay @ V, Max CL $12.8\text{ns} \otimes 3.3\text{V}$, 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Series	74LVX
Number of Inputs 2 Features - Voltage - Supply 2 $V \sim 3.6 V$ Current - Quiescent (Max) 2 μ A Current - Output High, Low 4mA, 4mA Logic Level - Low 0.5 $V \sim 0.8 V$ Logic Level - High 1.5 $V \sim 2.4 V$ Max Propagation Delay @ V , Max CL 12.8ns @ 3.3 V , 50pF Operating Temperature -40°C $\sim 85^{\circ}$ C Mounting Type Surface Mount	Logic Type	XOR (Exclusive OR)
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Number of Circuits	4
Voltage - Supply $2\ V \sim 3.6\ V$ $Current - Quiescent (Max) 2\mu A Current - Output High, Low 4mA, 4mA Logic Level - Low \\ Logic Level - High 1.5\ V \sim 2.4\ V Max\ Propagation\ Delay\ @V, Max\ CL \\ Operating\ Temperature -40^{\circ}C \sim 85^{\circ}C Mounting\ Type Surface\ Mount$	Number of Inputs	2
Current - Quiescent (Max) $2\mu A$ Current - Output High, Low $4mA, 4mA$ Logic Level - Low $0.5 \ V \sim 0.8 \ V$ Logic Level - High $1.5 \ V \sim 2.4 \ V$ Max Propagation Delay @ V, Max CL $12.8ns \ @ \ 3.3V, 50pF$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type $Surface \ Mount$	Features	-
Current - Output High, Low 4mA , 4mA Logic Level - Low $0.5 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.5 \text{ V} \sim 2.4 \text{ V}$ Max Propagation Delay @ V, Max CL 12.8ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Voltage - Supply	2 V ~ 3.6 V
Logic Level - Low $0.5 \text{ V} \sim 0.8 \text{ V}$ Logic Level - High $1.5 \text{ V} \sim 2.4 \text{ V}$ Max Propagation Delay @ V, Max CL $12.8 \text{ns} \otimes 3.3 \text{V}$, 50pF Operating Temperature $-40 ^{\circ}\text{C} \sim 85 ^{\circ}\text{C}$ Mounting TypeSurface Mount	Current - Quiescent (Max)	2μΑ
Logic Level - High $1.5 \text{ V} \sim 2.4 \text{ V}$ Max Propagation Delay @ V, Max CL 12.8ns @ 3.3V , 50pF Operating Temperature $-40 ^{\circ}\text{C} \sim 85 ^{\circ}\text{C}$ Mounting TypeSurface Mount	Current - Output High, Low	4mA, 4mA
Max Propagation Delay @ V, Max CL12.8ns @ 3.3V, 50pFOperating Temperature-40°C ~ 85°CMounting TypeSurface Mount	Logic Level - Low	0.5 V ~ 0.8 V
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Logic Level - High	1.5 V ~ 2.4 V
Mounting Type Surface Mount	Max Propagation Delay @ V, Max CL	12.8ns @ 3.3V, 50pF
C 71	Operating Temperature	-40°C ~ 85°C
Supplier Device Package 14-SOIC	Mounting Type	Surface Mount
	Supplier Device Package	14-SOIC
Package / Case 14-SOIC (0.209", 5.30mm Width)	Package / Case	14-SOIC (0.209", 5.30mm Width)
Report errors?		Report errors?

74LVX86SJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

74LVX86SJ Payment Methods





















74LVX86SJ Shipping Methods













If you have any question about 74LVX86SJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com