

75-194628-51S Information

Heisener.com

75-194628-51S Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG W/SOCKETS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









75-194628-51S Specifications

Manufacturer Part Number75-194628-51SManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions12Shell Size - Insert28-51Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 28-51 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Manufacturer Part Number	75-194628-51S
Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 28-51 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated Current Rating - Circular Connectors MIL-DTL-22992, QWLD Plug, Female Sockets MIL-DTL-22992, QWLD Plug, Female Sockets NIL-DTL-22992, QWLD Plug, Female Sockets Number Of Semale Sockets N	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 28-51 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating	Category	Connectors, Interconnects
Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 28-51 Shell Size, MIL		Circular Connectors
Connector Type Plug, Female Sockets Number of Positions 12 Shell Size - Insert 28-51 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Package	-
Number of Positions Shell Size - Insert 28-51 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated Current Rating - 12 28-51 - 28-51 - 4- 28-51 - 5- 28-51 - 5- 28-51 - 5- 28-51 - 5- 28-51 - 5- 28-51 - 5- 28-51 - 5- 28-51 - 5- 5- 5- 5- 5- 5- 5- 5-	Series	MIL-DTL-22992, QWLD
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated Current Rating - 28-51 - Silver Free Hanging (In-Line) Free Hanging (In-Line) Aluminum Crimp Aluminum Anodic Coating (Alumilite) Silver Footward Footw	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Voltage - Rated Current Rating - Contact Finish - Current Rating - Shell Material Silver - Current Rating - Silver - Current Rating - Silver - Silver - Silver - Silver - Silver - Silver - Current Rating - Silver -	Number of Positions	12
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	28-51
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Crimp
Ingress Protection Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Waterproof Aluminum, Anodic Coating (Alumilite) Silver - - - - - - - - - - - - -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite) 500VAC, 700VDC -	Orientation	N (Normal)
Contact Finish Features Voltage - Rated Current Rating Silver - - 500VAC, 700VDC -	Ingress Protection	Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
•	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

75-194628-51S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

75-194628-51S Payment Methods





















75-194628-51S Shipping Methods













If you have any question about 75-194628-51S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com