

75-194632-17S Information

Heisener.com

75-194632-17S Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG W/SOCKETS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









75-194632-17S Specifications

Manufacturer Part Number75-194632-17SManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert32-17Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Manufacturer Part Number	75-194632-17S
Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 32-17 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 32-17 Shell Size, MIL - Crimp Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating	Category	Connectors, Interconnects
Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 4 Shell Size - Insert 32-17 Shell Size, MIL		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions4Shell Size - Insert32-17Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 32-17 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Series	MIL-DTL-22992, QWLD
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Voltage - Rated 900VAC, 1250VDC Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features Voltage - Rated 900VAC, 1250VDC Current Rating -	Number of Positions	4
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size - Insert	32-17
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Crimp
Ingress Protection Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Waterproof Aluminum, Anodic Coating (Alumilite) Silver - - Voltage - Rated 900VAC, 1250VDC -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite) Silver - Current Rating	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Ingress Protection	Waterproof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

75-194632-17S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

75-194632-17S Payment Methods





















75-194632-17S Shipping Methods













If you have any question about 75-194632-17S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com