

752241102G Information

Part Number 752241102G

Manufacturer CTS Resistor Products

Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 22 RES 1K OHM 24DRT

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









752241102G Specifications

Manufacturer Part Number 752241102G Manufacturer CTS Resistor Products Category Resistors Resistor Networks, Arrays Package 24-DRT Series 752 Circuit Type Bussed Resistance (Ohms) 1k Tolerance ±2% Number of Resistors 22 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm) Report errors?		
Category Resistors Package 24-DRT Series 752 Circuit Type Bussed Resistance (Ohms) 1k Tolerance ±2% Number of Resistors 22 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Manufacturer Part Number	752241102G
Package 24-DRT Series 752 Circuit Type Bussed Resistance (Ohms) 1k Tolerance ±2% Number of Resistors 22 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Manufacturer	CTS Resistor Products
Package 24-DRT Series 752 Circuit Type Bussed Resistance (Ohms) 1k Tolerance ±2% Number of Resistors 22 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Category	Resistors
Series 752 Circuit Type Bussed Resistance (Ohms) 1k Tolerance ±2% Number of Resistors 22 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)		Resistor Networks, Arrays
Circuit TypeBussedResistance (Ohms)1kTolerance±2%Number of Resistors22Number of Pins24Power Per Element80mWTemperature Coefficient±200ppm/°COperating Temperature-55°C ~ 125°CApplications-Mounting TypeSurface MountPackage / Case24-DRTSupplier Device Package-Size / Dimension0.665" L x 0.080" W (16.89mm x 2.03mm)Height - Seated (Max)0.100" (2.53mm)	Package	24-DRT
Resistance (Ohms) 1k Tolerance ±2% Number of Resistors 22 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Series	752
Tolerance ±2% Number of Resistors 22 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Circuit Type	Bussed
Number of Resistors 24 Power Per Element 80mW Temperature Coefficient -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package Size / Dimension Height - Seated (Max) 24 80mW -24 80mW -250ppm/°C -55°C ~ 125°C -	Resistance (Ohms)	1k
Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Tolerance	±2%
Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Number of Resistors	22
Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Number of Pins	24
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Power Per Element	80mW
Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Temperature Coefficient	±200ppm/°C
Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Applications	-
Supplier Device Package - Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Mounting Type	Surface Mount
Size / Dimension 0.665" L x 0.080" W (16.89mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Package / Case	24-DRT
Height - Seated (Max) 0.100" (2.53mm)	Supplier Device Package	-
	Size / Dimension	0.665" L x 0.080" W (16.89mm x 2.03mm)
Report errors?	Height - Seated (Max)	0.100" (2.53mm)
		Report errors?

752241102G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

752241102G Payment Methods



















752241102G Shipping Methods













If you have any question about 752241102G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com