



753243101GPTR7 Information

Heisener.com

Part Number 753243101GPTR7

Manufacturer CTS Resistor Products

Category Resistors

Resistor Networks, Arrays

Description RES ARRAY 12 RES 100 OHM 24DRT

Package 24-DRT

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









753243101GPTR7 Specifications

Manufacturer Part Number 753243101GPTR7 Manufacturer CTS Resistor Products Category Resistors Resistor Networks, Arrays Package 24-DRT Series 753 Circuit Type Isolated Resistance (Ohms) 100 Tolerance ±2% Number of Resistors 12 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm) Report errors?		
Category Resistor Networks, Arrays Package 24-DRT Series 753 Circuit Type Isolated Resistance (Ohms) 100 Tolerance ±2% Number of Resistors 12 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Manufacturer Part Number	753243101GPTR7
Resistor Networks, Arrays Package 24-DRT Series 753 Circuit Type Isolated Resistance (Ohms) 100 Tolerance ±2% Number of Resistors 12 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Manufacturer	CTS Resistor Products
Package 24-DRT Series 753 Circuit Type Isolated Resistance (Ohms) 100 Tolerance ±2% Number of Resistors 12 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Category	Resistors
Series 753 Circuit Type Isolated Resistance (Ohms) 100 Tolerance ±2% Number of Resistors 12 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)		Resistor Networks, Arrays
Circuit Type Isolated Resistance (Ohms) 100 Tolerance ±2% Number of Resistors 12 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Package	24-DRT
Resistance (Ohms) 100 Tolerance ±2% Number of Resistors 12 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Series	753
Tolerance ±2% Number of Resistors 12 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Circuit Type	Isolated
Number of Resistors 12 Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Resistance (Ohms)	100
Number of Pins 24 Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Tolerance	±2%
Power Per Element 80mW Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Number of Resistors	12
Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Number of Pins	24
Operating Temperature -55°C ~ 125°C Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Power Per Element	$80 \mathrm{mW}$
Applications - Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Temperature Coefficient	±200ppm/°C
Mounting Type Surface Mount Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Operating Temperature	-55°C ~ 125°C
Package / Case 24-DRT Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Applications	-
Supplier Device Package - Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Mounting Type	Surface Mount
Size / Dimension 0.345" L x 0.080" W (8.76mm x 2.03mm) Height - Seated (Max) 0.100" (2.53mm)	Package / Case	24-DRT
Height - Seated (Max) 0.100" (2.53mm)	Supplier Device Package	-
	Size / Dimension	0.345" L x 0.080" W (8.76mm x 2.03mm)
Report errors?	Height - Seated (Max)	0.100" (2.53mm)
		Report errors?

753243101GPTR7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

753243101GPTR7 Payment Methods



















753243101GPTR7 Shipping Methods













If you have any question about 753243101GPTR7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com