



### 76051-B00000020-01 Information



For Reference Only

Part Number 76051-B00000020-01

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** SWITCH PRESSURE N.O. 2PSI

Package Cylinder, Threaded

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## 76051-B00000020-01 Specifications

Manufacturer Part Number         76051-B0000020-01           Manufacturer         Honeywell Sensing and Productivity Solutions           Category         Sensors, Transducers           Package         Cylinder, Threaded           Series         5000           Pressure Type         Switch           Operating Pressure         2 PSI (13.79 kPa)           Output Type         SPST-NC (1) NO (1)           Output         -           Accuracy         -           Voltage - Supply         -           Port Size         Male - 1/8" (3.18mm) NPT           Port Style         Threaded           Features         -           Termination Style         Screw Terminal           Maximum Pressure         150 PSI (1034.21 kPa)           Operating Temperature         -40°C ~ 121°C           Package / Case         Cylinder, Threaded           Supplier Device Package         -		
CategorySensors, TransducersPackageCylinder, ThreadedSeries5000Pressure TypeSwitchOperating Pressure2 PSI (13.79 kPa)Output TypeSPST-NC (1) NO (1)Output-Accuracy-Voltage - Supply-Port SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure150 PSI (1034.21 kPa)Operating Temperature-40°C ~ 121°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Manufacturer Part Number	76051-B00000020-01
PackageCylinder, ThreadedSeries5000Pressure TypeSwitchOperating Pressure2 PSI (13.79 kPa)Output TypeSPST-NC (1) NO (1)Output-Accuracy-Voltage - Supply-Port SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure150 PSI (1034.21 kPa)Operating Temperature-40°C ~ 121°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinder, ThreadedSeries5000Pressure TypeSwitchOperating Pressure2 PSI (13.79 kPa)Output TypeSPST-NC (1) NO (1)Output-Accuracy-Voltage - Supply-Port SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure150 PSI (1034.21 kPa)Operating Temperature-40°C ~ 121°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Category	Sensors, Transducers
Series         5000           Pressure Type         Switch           Operating Pressure         2 PSI (13.79 kPa)           Output Type         SPST-NC (1) NO (1)           Output         -           Accuracy         -           Voltage - Supply         -           Port Size         Male - 1/8" (3.18mm) NPT           Port Style         Threaded           Features         -           Termination Style         Screw Terminal           Maximum Pressure         150 PSI (1034.21 kPa)           Operating Temperature         -40°C ~ 121°C           Package / Case         Cylinder, Threaded           Supplier Device Package         -		Pressure Sensors, Transducers
Pressure TypeSwitchOperating Pressure2 PSI (13.79 kPa)Output TypeSPST-NC (1) NO (1)Output-Accuracy-Voltage - Supply-Port SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure150 PSI (1034.21 kPa)Operating Temperature-40°C ~ 121°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Package	Cylinder, Threaded
Operating Pressure 2 PSI (13.79 kPa) Output Type SPST-NC (1) NO (1) Output - Accuracy - Voltage - Supply - Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features - Termination Style Screw Terminal Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 121°C Package / Case Cylinder, Threaded Supplier Device Package -	Series	5000
Output Type SPST-NC (1) NO (1) Output - Accuracy - Voltage - Supply - Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features - Termination Style Screw Terminal Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 121°C Package / Case Cylinder, Threaded Supplier Device Package -	Pressure Type	Switch
Output - Accuracy  Voltage - Supply  Port Size Male - 1/8" (3.18mm) NPT  Port Style Threaded  Features  Termination Style Screw Terminal  Maximum Pressure 150 PSI (1034.21 kPa)  Operating Temperature -40°C ~ 121°C  Package / Case Cylinder, Threaded  Supplier Device Package	Operating Pressure	2 PSI (13.79 kPa)
Accuracy  Voltage - Supply  - Port Size  Male - 1/8" (3.18mm) NPT  Port Style  Threaded  Features  - Termination Style  Screw Terminal  Maximum Pressure  150 PSI (1034.21 kPa)  Operating Temperature  Package / Case  Cylinder, Threaded  Supplier Device Package  -	Output Type	SPST-NC (1) NO (1)
Voltage - Supply  Port Size  Male - 1/8" (3.18mm) NPT  Port Style  Threaded  Features  - Termination Style  Screw Terminal  Maximum Pressure  150 PSI (1034.21 kPa)  Operating Temperature  -40°C ~ 121°C  Package / Case  Cylinder, Threaded  Supplier Device Package  -	Output	-
Port Size Male - 1/8" (3.18mm) NPT  Port Style Threaded  Features -  Termination Style Screw Terminal  Maximum Pressure 150 PSI (1034.21 kPa)  Operating Temperature -40°C ~ 121°C  Package / Case Cylinder, Threaded  Supplier Device Package -	Accuracy	-
Port Style Threaded  Features -  Termination Style Screw Terminal  Maximum Pressure 150 PSI (1034.21 kPa)  Operating Temperature -40°C ~ 121°C  Package / Case Cylinder, Threaded  Supplier Device Package -	Voltage - Supply	-
Features - Cremination Style Screw Terminal Screw Terminal Style Screw Terminal 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 121°C Package / Case Cylinder, Threaded Supplier Device Package -	Port Size	Male - 1/8" (3.18mm) NPT
Termination Style Screw Terminal  Maximum Pressure 150 PSI (1034.21 kPa)  Operating Temperature -40°C ~ 121°C  Package / Case Cylinder, Threaded  Supplier Device Package -	Port Style	Threaded
Maximum Pressure 150 PSI (1034.21 kPa)  Operating Temperature -40°C ~ 121°C  Package / Case Cylinder, Threaded  Supplier Device Package -	Features	-
Operating Temperature -40°C ~ 121°C  Package / Case Cylinder, Threaded  Supplier Device Package -	Termination Style	Screw Terminal
Package / Case Cylinder, Threaded Supplier Device Package -	Maximum Pressure	150 PSI (1034.21 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 121°C
	Package / Case	Cylinder, Threaded
Report errors?	Supplier Device Package	-
		Report errors

#### 76051-B00000020-01 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 76051-B00000020-01 Payment Methods





















## **76051-B00000020-01 Shipping Methods**













If you have any question about 76051-B00000020-01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com